

MIRA-W

~40° wide beam

SPECIFICATION:

Dimensions	Ø 32.4 mm
Height	14.7 mm
Fastening	glue
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
MIRA-W	Single lens	PC	clear	



ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C12501_MIRA-W » Box size: 480 x 280 x 300 mm	840	120	60	7.2




See also our general installation guide: www.ledil.com/installation_guide


OPTICAL RESULTS (MEASURED):



LED BXRA ES Star
FWHM / FWTM 39.0° / 76.0°
Efficiency 82 %
LEDs/each optic 1
Light colour White
Required components:





LED V10 Gen6
FWHM / FWTM 44.0° / 82.0°
Efficiency 77 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED CXA/B 15xx
FWHM / FWTM 39.0° / 77.0°
Efficiency 80 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED MHD-E/G
FWHM / FWTM 43.0° / 83.0°
Efficiency 81 %
Peak intensity 1.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):




LED MT-G
FWHM / FWTM 38.0° / 78.0°
Efficiency 80 %
Peak intensity 1.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XHP70
FWHM / FWTM 42.0° / 81.0°
Efficiency 80 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON M/MX
FWHM / FWTM 39.0° / 78.0°
Efficiency 82 %
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON MZ
FWHM / FWTM 31.0° / 67.0°
Efficiency 79 %
Peak intensity 2 cd/lm
LEDs/each optic 1
Light colour White
Required components:





OPTICAL RESULTS (MEASURED):





LED NFMW48xA
FWHM / FWTM 32.0° / 68.0°
Efficiency 80 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED NSCxL036A
FWHM / FWTM 42.0° / 77.0°
Efficiency 79 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NSMx286M
FWHM / FWTM 28.0° / 63.0°
Efficiency 77 %
Peak intensity 2.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED Duris S10
FWHM / FWTM 34.0° / 74.0°
Efficiency 83 %
Peak intensity 1.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:





Detector image: illuminance	
01-0-0004 Detector: 7-000 Surface 1 Size: 1000 lines x 1000 lines x 1000 lines, Pixels: 1000 x 1000, Total size: 800000 Resolution: 1000 lines x 1000 lines Total Time: 0.000000 seconds	C:\MSD\DATA\01-0-0004_P01.tif Color mode: 24-bit



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)