

DO NOT
SCALE FROM
THIS PRINT

TABLE 1			
No. OF POS	"A"	"B"	"C"
-10	5.25 [0.207]	4.500 [0.1772]	6.42 [0.253]
-15	7.75 [0.305]	7.000 [0.2756]	8.92 [0.351]
-20	10.25 [0.404]	9.500 [0.3740]	11.42 [0.450]
-30	15.25 [0.600]	14.500 [0.5709]	16.42 [0.646]
-40	20.25 [0.797]	19.500 [0.7677]	21.42 [0.843]
-50	25.25 [0.994]	24.500 [0.9646]	26.42 [1.040]
-60	30.25 [1.191]	29.500 [1.1614]	31.42 [1.237]
-70	35.25 [1.388]	34.500 [1.3583]	36.42 [1.434]
-80	40.25 [1.585]	39.500 [1.5551]	41.42 [1.631]

DESIGNED & DIMENSIONED
IN MILLIMETERS[INCHES]

ST5-XX-X.XX-X-D-P-XR

No OF POSITIONS
-10, -15, -20, -30, -40,
-50, -60, -70, -80 (PER ROW)

TAPE & REEL (SEE NOTES 4 & 5)
-TR: TAPE & REEL
-FR: FULL REEL QTY TAPE & REEL


LEAD STYLE
-1.00: (USE T-1M50-1.00-L)
-1.50: (USE T-1M50-1.50-L)
*-2.50: (USE T-1M50-2.50-L)

PLACEMENT PAD
-P: PICK AND PLACE PAD
(SEE FIG 4, SHT 2)
(-10, -20, -30, -40, -50, -60, -70, -80
USE PPP-65-01, -15 USE PPP-65-02)

PLATING SPECIFICATION
-L: 10µ" SELECTIVE GOLD IN CONTACT
AREA, MATTE TIN ON TAIL

ROW SPECIFICATION
-D: DOUBLE

(* = NOT TOOLED)



DIE ROLL TO FACE
POSITION 1 END


DETAIL 'B'
SCALE 20 : 1

TABLE 2 REF		
STACK HEIGHT		
ST5 LEAD STYLE	SS5 LEAD STYLE	
-1.00	-3.00	-3.50
-1.50	4.0 [0.16]	4.5 [0.18]
-1.50	4.5 [0.18]	5.0 [0.20]
-2.50	5.5 [0.22]	6.0 [0.24]




SECTION "A"-A"
SCALE 10 : 1

TABLE 3					
LEAD STYLE	"D"	"E"	"F"	BODY	TERMINAL
-1.00	1.00 [0.039]	3.08 [0.121]	0.80 [0.031]	ST5-XX-1.00-D	T-1M50-1.00-X
-1.50	1.50 [0.059]	3.58 [0.141]	0.80 [0.031]	ST5-XX-1.00-D	T-1M50-1.50-X
-2.50	2.50 [0.098]	4.58 [0.180]	1.80 [0.071]	ST5-XX-2.50-D	T-1M50-2.50-X

FIG 1
ST5-20-1.00-X-D-P-XR SHOWN

NOTES:

1. Ⓢ REPRESENTS A CRITICAL DIMENSION.
2. MINIMUM PUSHOUT FORCE: SIGNAL: 1.11N[0.25 LB].
3. NOTE DELETED.
4. ORDERS WILL BE PACKAGED ACCORDING TO THE SAMTEC PACKAGING EFFICIENCY STANDARDS (SPES) FOUND ON WWW.SAMTEC.COM.
5. ATTACH LABEL-4X2 TO EACH REEL.

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN MILLIMETERS.

TOLERANCES ARE:

DECIMALS ANGLES
X.X: ±0.3 [0.1]
X.XX: ±0.13 [0.05]
X.XXX: ±0.051 [0.020]

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS CONFIDENTIAL AND
PROPRIETARY INFORMATION AND ALL DESIGN,
MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS
AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC,
INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE
OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR
REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY
OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS
WRITTEN CONSENT OF SAMTEC, INC.

MATERIAL: DO NOT SCALE DRAWING
INSULATOR: LCP, UL 94 V0, COLOR: BLACK
TERMINAL: PHOS BRONZE

SHEET SCALE: 2:1

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION:

0.5mm TERMINAL STRIP ASSEMBLY

DWG. NO.

ST5-XX-X.XX-X-D-P-XR

BY: ROY LUO 03/29/2012 SHEET 1 OF 2

FIG 2
-1.50 LEAD STYLE
ST5-20-1.50-X-D-P-XR SHOWN
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)




FIG 3
-2.50 LEAD STYLE
ST5-20-2.50-X-D-P-XR SHOWN
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)




FIG 4
-P: PICK AND PLACE PAD OPTION
ST5-20-1.00-X-D-P-XR SHOWN
(DIFFERENT AS SHOWN, OTHERWISE SAME AS FIG 1)

TABLE 4	
LEAD STYLE	"G"
-1.00	3.58 [0.141]
-1.50	4.08 [0.161]
-2.50	5.08 [0.200]

TABLE 5	
No OF POS	"H"
-10	1.80 [0.071]
-15	3.22 [0.127]
-20	4.30 [0.169]
-30	6.80 [0.268]
-40	9.30 [0.366]
-50	11.80 [0.465]
-60	14.30 [0.563]
-70	16.80 [0.661]
-80	19.30 [0.760]

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND ALL DESIGN, MANUFACTURING, REPRODUCTION, USE, PATENT RIGHTS AND SALES RIGHTS ARE EXPRESSLY RESERVED BY SAMTEC, INC. THIS DOCUMENT SHALL NOT BE DISCLOSED, IN WHOLE OR PART, TO ANY UNAUTHORIZED PERSON OR ENTITY NOR REPRODUCED, TRANSFERRED OR INCORPORATED IN ANY OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING
SHEET SCALE: 5:1



520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION:
0.5mm TERMINAL STRIP ASSEMBLY

DWG. NO.
ST5-XX-X.XX-X-D-P-XR

BY: ROY LUO 03/29/2012 SHEET 2 OF 2