

# VIP/U/RAIL 3L DIVIDER - Partition plate



2908555

<https://www.phoenixcontact.com/pc/products/2908555>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VIP I/O marshalling partition plate for safe isolation between non-Ex i and Ex i assembled base modules for Honeywell systems. The partition plate is mounted directly on the DIN rail at the end of the base module.

## Your advantages

- Rail mounted divider at the end of the VIP base module provides separation between circuits

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2908555                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | CK8931                         |
| Catalog page                         | Page 553 (C-5-2017)            |
| GTIN                                 | 4055626408163                  |
| Weight per piece (including packing) | 20.1 g                         |
| Weight per piece (excluding packing) | 20.1 g                         |
| Customs tariff number                | 85389099                       |
| Country of origin                    | US                             |

# VIP/U/RAIL 3L DIVIDER - Partition plate



2908555

<https://www.phoenixcontact.com/pc/products/2908555>

## Technical data

### Product properties

|                |                     |
|----------------|---------------------|
| Product type   | Partition plate     |
| Product family | VIP I/O-Marshalling |

### Ambient conditions

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Ambient temperature (operation)         | -40 °C ... 75 °C              |
| Ambient temperature (storage/transport) | -40 °C ... 75 °C              |
| Permissible humidity (operation)        | 0 % ... 95 % (non-condensing) |

### Material specifications

|          |                 |
|----------|-----------------|
| Color    | gray (RAL 7042) |
| Material | PA 6.6          |

### Dimensions

|        |          |
|--------|----------|
| Width  | 5 mm     |
| Height | 136.7 mm |
| Depth  | 88.2 mm  |

### Environmental and real-life conditions

#### Ambient conditions

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Ambient temperature (operation)         | -40 °C ... 75 °C              |
| Ambient temperature (storage/transport) | -40 °C ... 75 °C              |
| Permissible humidity (operation)        | 0 % ... 95 % (non-condensing) |

# VIP/U/RAIL 3L DIVIDER - Partition plate



2908555

<https://www.phoenixcontact.com/pc/products/2908555>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27371392 |
| ECLASS-12.0 | 27371392 |
| ECLASS-13.0 | 27371392 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002498 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121100 |
|-------------|----------|

# VIP/U/RAIL 3L DIVIDER - Partition plate



2908555

<https://www.phoenixcontact.com/pc/products/2908555>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)