

CUC-PPC-C2ZNI-SEAL - Seal

1002405

<https://www.phoenixcontact.com/us/products/1002405>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Set of seals for push-pull Advance Power, for use with cable diameters 6.5 mm ... 9.5 mm.



Commercial data

Item number	1002405
Packing unit	5 pc
Note	Made to order (non-returnable)
Sales key	AB17
Product key	ABNOHZ
GTIN	4055626468747
Weight per piece (including packing)	3.57 g
Weight per piece (excluding packing)	4.03 g
Customs tariff number	39174000
Country of origin	DE

CUC-PPC-C2ZNI-SEAL - Seal



1002405

<https://www.phoenixcontact.com/us/products/1002405>

Technical data

Notes

General	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
---------	---

Dimensions

Width	19 mm
Height	19 mm
Length	15.5 mm

Material specifications

Seal material	NBR
---------------	-----

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-10 °C ... 40 °C

CUC-PPC-C2ZNI-SEAL - Seal



1002405

<https://www.phoenixcontact.com/us/products/1002405>

Classifications

ECLASS

ECLASS-11.0	27440101
ECLASS-12.0	27440392
ECLASS-13.0	27440392

ETIM

ETIM 8.0	EC002636
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CUC-PPC-C2ZNI-SEAL - Seal

1002405

<https://www.phoenixcontact.com/us/products/1002405>



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

CUC-PPC-C2ZNI-SEAL - Seal

1002405

<https://www.phoenixcontact.com/us/products/1002405>



Accessories

CUC-PPC-C2ZNI-SX/24FKP5 - Power connector

1421783

<https://www.phoenixcontact.com/us/products/1421783>



Power connector, design: Version 14, degree of protection: IP65/IP67, number of positions: 5, material: Metal, connection method: Spring-cage connection, connection cross section: AWG 18- 13, cable outlet: straight, Universal

CUC-PPC-C2ZNI-SX/24FKP5:FC - Power connector

1425514

<https://www.phoenixcontact.com/us/products/1425514>



Power connector, degree of protection: IP65/IP67, number of positions: 5, material: Metal, connection method: Spring-cage connection, connection cross section: AWG 18- 13, cable outlet: straight, Universal

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com