

Product data sheet

Specifications



Fuse carrier, TeSys DF, 1P+N,
32A, 690VAC, fuse size 10x38 mm

DF101N

Main

Range	TeSys
Product Name	TeSys DF
Product Or Component Type	Fuse carrier
Device Short Name	DF10
Device Composition	tubular link locked in Neutral pole
Product Compatibility	DF2CA fuse cartridge DF2CN fuse cartridge
Poles Description	1P + N
Fuse Size	10 x 38 mm
Fuse Type	, aM , gG
Control Type	Toggle padlockable
Utilisation Category	AC-20B IEC 60947-3 DC-20B IEC 60947-3
[Ue] Rated Operational Voltage	690 V AC 690 V DC
[Ie] Rated Operational Current	32 A 400 V AC
[Ith] Conventional Free Air Thermal Current	32 A 68 °F (20 °C)
[Ui] Rated Insulation Voltage	690 V AC
[Uimp] Rated Impulse Withstand Voltage	6 kV
Overvoltage Category	III
Short-Circuit Withstand	120 kA 400 V IEC 60947-3 120 kA 500 V IEC 60947-3
Power Dissipation In W	3 W maximum power dissipation by fuse

Complementary

Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1 EN 45545-2 R22 HL2
Product Certifications	IEC UL recognized CSA CCC EAC DNV-GL
Mounting Support	35 mm symmetrical DIN rail

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Position	Vertical +/- 23°)
Connections - Terminals	screw clamp terminals 1 0.00...0.02 in² (1...16 mm²)rigid screw clamp terminals 2 0.00...0.01 in² (1...6 mm²)rigid screw clamp terminals 1 0.00...0.02 in² (1...16 mm²)flexible with or without screw clamp terminals 2 0.00...0.01 in² (1...6 mm²)flexible with or without
Tightening Torque	19.47 lbf.in (2.2 N.m) PZ2 19.47 lbf.in (2.2 N.m) flat Ø 5.5 mm
Height	3.13 in (79.5 mm)
Width	1.38 in (35 mm)
Depth	2.40 in (61 mm)
Net Weight	0.19 lb(US) (0.087 kg)
Quantity Per Set	Set of 6

Environment

Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)
Ambient Air Temperature For Operation	-40...158 °F (-40...70 °C) with derating above 20°C
Operating Altitude	0...2000 m
Ip Degree Of Protection	IP20
Pollution Degree	3
Fire Resistance	1760 °F (960 °C) IEC 60695-2-1
Compatibility Code	DF10

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.38 in (3.5 cm)
Package 1 Width	2.44 in (6.2 cm)
Package 1 Length	3.15 in (8 cm)
Package 1 Weight	3.25 oz (92 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	6
Package 2 Height	2.68 in (6.8 cm)
Package 2 Width	3.35 in (8.5 cm)
Package 2 Length	8.74 in (22.2 cm)
Package 2 Weight	20.60 oz (584 g)
Unit Type Of Package 3	S03
Number Of Units In Package 3	96
Package 3 Height	11.81 in (30 cm)
Package 3 Width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
Package 3 Weight	21.79 lb(US) (9.885 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations End of Life Information