

HB-IP-2X6-RS

~20° spot beam

SPECIFICATION:

Dimensions	173.0 x 71.4 mm
Height	11.4 mm
Fastening	pin, screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
HB-IP-2X6-RS	Multi-lens	PMMA	clear	
2X6-SEAL25	Seal	Silicone	white	



ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CS14895_HB-IP-2X6-RS	Multi-lens	120	40	40	8.0
» Box size: 476 x 273 x 247 mm					




See also our general installation guide: www.ledil.com/installation_guide


OPTICAL RESULTS (MEASURED):




LED QUICK FLUX 2x6 LED XG xxx G7+
 FWHM / FWTM 16.0° / 33.0°
 Efficiency 94 %
 Peak intensity 7.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED QUICK FLUX 2x6 LED XT xxx G5
 FWHM / FWTM 13.0° / 26.0°
 Efficiency 94 %
 Peak intensity 10.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XM-L
 FWHM / FWTM 21.0° / 38.0°
 Efficiency 94 %
 Peak intensity 5.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED XP-G2
 FWHM / FWTM 13.0° / 27.0°
 Efficiency 94 %
 Peak intensity 10.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):




LED XP-L HD
 FWHM / FWTM 20.0° / 37.0°
 Efficiency 93 %
 Peak intensity 5.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




LED XP-L2
 FWHM / FWTM 22.0° / 43.0°
 Efficiency 93 %
 Peak intensity 4.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED XT-E HE
 FWHM / FWTM 13.0° / 26.0°
 Efficiency 94 %
 Peak intensity 11.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED LUXEON T
 FWHM / FWTM 15.0° / 29.0°
 Efficiency 94 %
 Peak intensity 8.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):


LUMILEDS

LED LUXEON V
FWHM / FWTM 20.0° / 41.0°
Efficiency 92 %
Peak intensity 4.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LUMILEDS

LED LUXEON V2
FWHM / FWTM 15.0° / 30.0°
Efficiency 94 %
Peak intensity 8.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LUMILEDS

LED LUXEON XR-TX (L2T0-xxxx012M0000)
FWHM / FWTM 14.0° / 27.0°
Efficiency 92 %
Peak intensity 10.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LUMINUS

LED SST-10-B130
FWHM / FWTM 12.0° / 22.0°
Efficiency 94 %
Peak intensity 15.6 cd/lm
LEDs/each optic 1
Light colour Deep Red
Required components:




OPTICAL RESULTS (MEASURED):

MST


Your solutions

LED RecLED 146x45mm 2900lm 730 2x6 IP G1
 FWHM / FWTM 14.0° / 27.0°
 Efficiency 95 %
 Peak intensity 10.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





NICHIA

LED NVSW219D
 FWHM / FWTM 16.0° / 30.0°
 Efficiency 94 %
 Peak intensity 8.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





NICHIA

LED NVSW219F
 FWHM / FWTM 16.0° / 31.0°
 Efficiency 8 %
 Peak intensity 94 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



NICHIA



LED NVSW319B
 FWHM / FWTM 18.0° / 34.0°
 Efficiency 94 %
 Peak intensity 6.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):





LED NVSW3x9A
FWHM / FWTM 19.0° / 36.0°
Efficiency 92 %
Peak intensity 5.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED NVSW519A
FWHM / FWTM 20.0° / 37.0°
Efficiency 95 %
Peak intensity 5.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxE21A
FWHM / FWTM 13.0° / 33.0°
Efficiency 94 %
Peak intensity 8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19B/NVSxx19C
FWHM / FWTM 16.0° / 32.0°
Efficiency 92 %
Peak intensity 7.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (MEASURED):

OSRAM


Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
FWHM / FWTM 13.0° / 24.0°
Efficiency 94 %
Peak intensity 12 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHILIPS

LED Fortimo FastFlex LED 2x6 DP G4
FWHM / FWTM 13.0° / 27.0°
Efficiency 94 %
Peak intensity 10.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHILIPS

LED Fortimo FastFlex LED 2x6 DP G5
FWHM / FWTM 14.0° / 26.0°
Efficiency 96 %
Peak intensity 10.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG



LED HiLOM RH12 (LH351C)
FWHM / FWTM 17.0° / 31.0°
Efficiency 94 %
Peak intensity 7.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (MEASURED):


SCIOLUX

LED BALAM-VP-5250-750-36
 FWHM / FWTM 22.0° / 50.0°
 Efficiency 95 %
 Peak intensity 3.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




SCIOLUX

LED BALAMEC-VE-5700-740-36
 FWHM / FWTM 23.0° / 50.0°
 Efficiency 96 %
 Peak intensity 3.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





SCIOLUX

LED XLE-S22C4XTEHE (XT-E HE)
 FWHM / FWTM 13.0° / 26.0°
 Efficiency 94 %
 Peak intensity 11.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SCIOLUX









LED XLE-S26XHP35 (XHP35 HD)
 FWHM / FWTM 24.0° / 45.0°
 Efficiency 94 %
 Peak intensity 3.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (MEASURED):

<p>SEOUL SEMICONDUCTOR</p> <p>LED 2x6 5050 module - SMJD-3625012F-XX</p> <p>FWHM / FWTM 24.0° / 53.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED SMJQ-D36W12Mx</p> <p>FWHM / FWTM 15.0° / 39.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 5.1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED SMJQ-D36W12Px</p> <p>FWHM / FWTM 16.0° / 36.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 6.3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z5M1/Z5M2</p> <p>FWHM / FWTM 14.0° / 26.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 10 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		



OPTICAL RESULTS (MEASURED):

<p>SEOUL SEMICONDUCTOR</p> <p>LED Z5M3</p> <p>FWHM / FWTM 16.0° / 33.0°</p> <p>Efficiency 95 %</p> <p>Peak intensity 7.3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22</p> <p>FWHM / FWTM 15.0° / 39.0°</p> <p>Efficiency 89 %</p> <p>Peak intensity 5.1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22P</p> <p>FWHM / FWTM 17.0° / 34.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 6.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>TRIDONIC</p> <p>LED RLE 2x6 3000lm HP EXC2 OTD</p> <p>FWHM / FWTM 13.0° / 25.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 11.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

OPTICAL RESULTS (MEASURED):

TRIDONIC


LED RLE 2x6 4500lm HP HE EXC3 OTD Z19
 FWHM / FWTM 24.0° / 50.0°
 Efficiency 96 %
 Peak intensity 3.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




OPTICAL RESULTS (SIMULATED):




LED J Series 5050 Round LES
 FWHM / FWTM 25.0° / 51.0°
 Efficiency 94 %
 Peak intensity 3.4 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:




LED J Series 5050B 6V K Class
 FWHM / FWTM 24.0° / 52.0°
 Efficiency 94 %
 Peak intensity 3.2 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:



LED XB-H
 FWHM / FWTM 12.0° / 28.0°
 Efficiency 92 %
 Peak intensity 10.6 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:




LED XHP35 HD
 FWHM / FWTM 22.0° / 46.0°
 Efficiency 93 %
 Peak intensity 3.8 cd/Im
 LEDs/each optic 1
 Light colour White
 Required components:




OPTICAL RESULTS (SIMULATED):




LED XHP35 HI
FWHM / FWTM 16.0° / 32.0°
Efficiency 93 %
Peak intensity 8.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XHP35.2 HD
FWHM / FWTM 26.0° / 48.0°
Efficiency 92 %
Peak intensity 3.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED XP-E2
FWHM / FWTM 11.0° / 26.0°
Efficiency 91 %
Peak intensity 14.1 cd/Im
LEDs/each optic 1
Light colour White
Required components:




LED XP-G2 HE
FWHM / FWTM 17.0° / 35.0°
Efficiency 93 %
Peak intensity 6.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED XP-G4
FWHM / FWTM 14.0° / 26.0°
Efficiency 93 %
Peak intensity 10.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XQ-E HD
FWHM / FWTM 8.0° / 19.0°
Efficiency 92 %
Peak intensity 21.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON 5050 Round LES
FWHM / FWTM 23.0° / 50.0°
Efficiency 91 %
Peak intensity 3.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON 5050 Square LES
FWHM / FWTM 25.0° / 52.0°
Efficiency 94 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):




LED LUXEON C
FWHM / FWTM 10.0° / 23.0°
Efficiency 91 %
Peak intensity 17.3 cd/lm
LEDs/each optic 1
Light colour Cyan
Required components:




LED NV4WB35AM
FWHM / FWTM 22.0° / 40.0°
Efficiency 94 %
Peak intensity 4.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED PrevaLED Brick HP IP 2x6
FWHM / FWTM 14.0° / 28.0°
Efficiency 92 %
Peak intensity 10.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED OSCONIQ C 2424
FWHM / FWTM 11.0° / 22.0°
Efficiency 93 %
Peak intensity 16.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):

OSRAM

Opto Semiconductors


LED OSCONIQ P 3030
FWHM / FWTM 9.0° / 20.0°
Efficiency 94 %
Peak intensity 21.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSCONIQ P 3737 (2W version)
FWHM / FWTM 12.0° / 25.0°
Efficiency 89 %
Peak intensity 13 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSCONIQ P 3737 (3W version)
FWHM / FWTM 19.0° / 37.0°
Efficiency 93 %
Peak intensity 6.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors

LED OSCONIQ P 3737 Flat
FWHM / FWTM 14.0° / 30.0°
Efficiency 94 %
Peak intensity 9.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:




OPTICAL RESULTS (SIMULATED):

OSRAM


Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3
FWHM / FWTM 10.0° / 20.0°
Efficiency 92 %
Peak intensity 20.2 cd/lm
LEDs/each optic 1
Light colour Far Red
Required components:




SAMSUNG

LED LH181B
FWHM / FWTM 13.0° / 28.0°
Efficiency 93 %
Peak intensity 10.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SAMSUNG

LED LH231B
FWHM / FWTM 16.0° / 32.0°
Efficiency 93 %
Peak intensity 8.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



SAMSUNG

LED LH351D
FWHM / FWTM 22.0° / 40.0°
Efficiency 93 %
Peak intensity 4.6 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OPTICAL RESULTS (SIMULATED):

<p>SEOUL SEMICONDUCTOR</p> <p>LED Z5M4</p> <p>FWHM / FWTM 16.0° / 34.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 7.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22T</p> <p>FWHM / FWTM 15.0° / 33.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 7.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)