




All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

RPC-1.35 side according to	IEC 61169-65
RPC-1.85 side	
According to	IEC 61169-32
Mechanically compatible with	RPC-2.40

Documents

N/A

Material and plating

Connector parts

Center conductor
Outer conductor
Dielectric

Material

CuBe
CuBe or equiv.
PS

Plating

Gold, min. 1.27µm
Gold, min. 1.27µm

Technical Data Sheet

Rosenberger

Adaptor
RPC-1.35 Jack – RPC-1.85 Plug

P9K108-S00D3

Electrical data

Frequency DC to 70 GHz
Return loss ≥ 28 dB, DC to 20 GHz
 ≥ 20 dB, 20 GHz to 50 GHz
 ≥ 17 dB, 50 GHz to 70 GHz

Mechanical data

	RPC-1.35	RPC-1.85
Mating cycles	≥ 3000	≥ 500
Maximum torque	1.65 Nm	1.65 Nm
Recommended torque	0.90 Nm	0.90 Nm
Gauge	0.003 mm to 0.020 mm	0.000 mm to 0.050 mm

Environmental data

Temperature range - 40 °C to +85 °C
RoHS compliant

Packing

Standard 1 pce in box
Weight 6.2 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Marcel Panicke	12.11.19	Lars Ramtke	02.04.20	a00	19-2316	Marcel Panicke	02.04.20
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2