ATGBICS Universally Coded MSA Compliant Transceiver SFP+ 32G Fibre Channel-SW (850nm, MMF, 100m, DOM, Ind Temp)

Brand : ATGBICS

Product code: SFP-32G-FC-SW-I-MSA-AT

Product name : ATGBICS Universally Coded MSA Compliant Transceiver SFP+ 32G Fibre Channel-SW

(850nm, MMF, 100m, DOM, Ind Temp)

AIGBICS
PROCESSIONAL AIGBICS
APPROXIMATION A

ATGBICS Universally Coded MSA Compliant Transceiver SFP+ 32G Fibre Channel-SW (850nm, MMF, 100m, DOM, Ind Temp)

ATGBICS Universally Coded MSA Compliant Transceiver SFP+ 32G Fibre Channel-SW (850nm, MMF, 100m, DOM, Ind Temp):

ATGBICS SFP-32G-FC-SW-I-MSA-AT Universally Coded MSA Compliant 32GBase-Fibre Channel supports a distance of up to 100m over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets all Multi-Source Agreement (MSA) standards for this form factor and are uniquely serialised for full date code and BOM traceability. We proudly offer a compatibility guarantee and lifetime replacement warranty.



Performance		Power	
SFP transceiver type * Fiber optic Maximum data transfer rate * 28050 Mbit/s Interface type * SFP28 Single-mode fiber (SMF) supported ✓	28050 Mbit/s	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	fiber (MMF) supported X connector LC iver standard SW ansfer distance 100 m 1310 nm N erface type 32 Gigabit Ethernet	Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN		Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 °C 85 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Ethernet interface type Digital Diagnostics Monitoring		Weight & dimensions	
(DDM)	1	Width	13.4 mm
Wavelength-division multiplexing (WDM)	×	Depth Height	56.5 mm 8.5 mm
Features		Weight	20 g
oduct colour Silver ousing material Metal ug and Play ot-Plug support	Packaging data Number of products included Package type	1 pc(s) Box	
Hot-swap	1	Technical details	
Easy to install Country of origin Brand compatibility Certification	United Kingdom MSA Compliant CE, FCC, RoHS	Sustainability compliance Sustainability certificates Doesn't contain	√ RoHS Lead



5056468773951

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.