ATGBICS Universally Coded MSA Compliant Transceiver CWDM SFP+ 10GBase (80km, SMF, LC 1490nm, DOM)

Brand: ATGBICS

Product code: CWDM-SFP-10G-1490-80-MSA-AT



Product name : Universally Coded MSA Compliant Transceiver CWDM SFP+ 10GBase (80km, SMF, LC 1490nm, DOM)

ATGBICS Universally Coded MSA Compliant Transceiver CWDM SFP+ 10GBase (80km, SMF, LC 1490nm, DOM)

ATGBICS Universally Coded MSA Compliant Transceiver CWDM SFP+ 10GBase (80km, SMF, LC 1490nm, DOM):

ATGBICS Universally Coded MSA Network Transceivers are specifically designed for use in 'open standard' platforms. Unlike some OEMs such as Cisco and HP, other network equipment manufacturers do not have specific firmware coding requirements for compatibility with their brand of networking equipment. This form of 'open coding' or 'generic coding' network infrastructure supports versatile purchasing options of network transceivers. Our plug and play Universally Coded Transceivers are also ideal for clients building their own bespoke infrastructure. Our product meets all Multi-Source Agreement (MSA) standards for this form factor and are uniquely serialised for full date code and BOM traceability. We proudly offer a compatibility guarantee and lifetime replacement warranty

		_	
Performance		Features	
SFP transceiver type *	Fiber optic	Certification	CE, FCC, RoHS
Interface type * SFP Single-mode fiber (SMF) supported 🗸	X LC	Power	
		Input voltage	3.3 V
		Maximum voltage	3.5 V
Multi-mode fiber (MMF) supported		Power consumption (typical)	1 W
SFP transceiver standard CWDM		1 (31)	
		Operational conditions	
Maximum transfer distance	80000 m	Maximum operating temperature	70 °C
Wavelength	1490 nm	Operating temperature (T-T)	0 - 70 °C
Coarse Wavelength Division	✓	Storage temperature (T-T)	-40 - 85 °C
Multiplexing (CWDM)	,	Operating relative humidity (H-H)	0 - 95%
Ethernet LAN	10 Circle II Filler and	Storage relative humidity (H-H)	0 - 95%
Ethernet interface type	10 Gigabit Ethernet	Weight & dimensions	
Digital Diagnostics Monitoring (DDM)	✓	Width	13.4 mm
Features		Depth	56.5 mm
Product colour	Silver Metal	Height Weight	8.5 mm
Housing material			20 g
Plug and Play	√	Packaging data	
Hot-swap	✓	Number of products included	1 pc(s)
Easy to install	✓	Package type	Blister
, ,	United Kingdom	Technical details	
	MSA Compliant	Sustainability compliance	✓
		Sustainability certificates	RoHS, Federal Communications Commission (FCC), CE, REACH
		Doesn't contain	Lead



5056468774460

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.