PCS.00.250.CTME31





Summary

Request a quote

Catalog	
Coax	1
Socket / Receptacle	Socket / Receptacle - Free
Locking system	Push-pull
Matching parts	FFS.00.250.CTCE31
Series	00 - NIM-CAMAC

Technical details

Electrical Configuration

Coax	1	
Contact Termination Coax	Crimp	
R (max)	6.1 mOhm	
Insert configuration value	0.25 - 1 Coax (50 Ohm)	
Insulator	T: PTFE	
Rated current	4 Amps	
Impedance	50 Ohm	
VSWR	1.09 + 0.11 * f/GHz	
Vtest	2100 V (AC), 3000 V (DC)	
Contact Type	Coaxial 50 Ohm (Crimp)	
Test voltage	2.1 kV (rms)	
Cable type	Storm 421-099	
Bucket Dia.	0.6 mm (0.024in)	
Contact Dia.	0.7 mm (0.028in)	

$\underline{https://www.lemo.com/int_en/solutions/specialties/00-nim-camac/pcs-00-250-ctme31.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Form & Material

Shell style / Model id	PCS - Free receptacle with cable crimping
Socket / Receptacle	Free
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Push-pull
Keying	Circular, female
Weight	3.75 g
Environment	
Environmental protection	IP50
F ret (min)	100 N
Salt Spray Corrosion	>1000 hr
Cable fixation	
Cable termination protection	Standard back nut (no additional protection)
Fixation type	Crimp

Recommended By Lemo

Accessories

Tools	
Die Tool	DPN.99.123.8K
Crimp tool	DPE.99.123.8K
Spanner wrench	DCP.99.055.TC

Cables

Cable PartNumber	Material	Colour	Cable image
17420	PVC	Black	
17450	COPOLYMER	Black	
178190	PTFE	Brown	
18700	PTFE	White	
18800	PTFE	White	
196270	PTFE	White	
31600	PTFE	Brown	
CCX.50.030.083.180B		white	
CCX.50.RG0.58AU14B	FEP	white	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.78BU18M	FEP	Brown	
CCX.50.RG1.78BU18M	PTFE	Brown	
CCX.50.RG1.88AU24B	TFE	white	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG1.96AU19B	PTFE	White	
CCX.50.RG1.96AU20B	PFA	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.50.RG3.16U28M	PTFE	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	- 8 -