



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Passivated
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours

| Connector dimension | |
|---------------------|-----------------|
| Dim | Nominal |
| A | 49.2±0.3 |
| B | 33.32+0.1/-0.15 |
| R | 32.5Max |
| S | 46±0.4 |
| W | 3+0.9/-0.1 |
| VV THREAD | M28x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D719K32SNL

| | | | |
|--------------|---|--------------------------------|---|
| A | 30-09-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Stainless Steel Receptacle 8D series | | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| NA | SOURIAU WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | A3 | | SOURIAU DRG N° 8D719K32SNL-C SHEET 1/2 |

| | | | | | | | | | | |
|----------------|------------------------|---|---|----|---|----|---|---|---|------------------------------------|
| BASIC SERIES: | 8D | 7 | - | 19 | K | 32 | S | N | L | Delivered W/O Contacts |
| SHELL TYPE : | Jam nut Receptacle | | | | | | | | | ORIENTATION : N |
| CONTACT TYPE : | Standard Crimp Contact | | | | | | | | | CONTACT TYPE : SOCKET(500 Matings) |
| SHELL SIZE : | 19 | | | | | | | | | CONTACT LAYOUT : 19-32 |
| PLATING : | K = Passivated | | | | | | | | | |

Contact Layout



| Contacts (insert arrangement 19-32) | | | | | |
|--|------------------|-------------|---------------------|------------------|-------------|
| Contact position ID | Contact location | | Contact position ID | Contact location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +066 (1.68) | +353 (8.97) | T | -066 (1.68) | +353 (8.97) |
| B | +189 (4.80) | +305 (7.75) | U | +000 (0.00) | +230 (5.84) |
| C | +286 (7.26) | +217 (5.51) | V | +124 (3.15) | +193 (4.90) |
| D | +345 (8.76) | +098 (2.49) | W | +209 (5.31) | +092 (2.41) |
| E | +357 (9.07) | -033 (0.84) | X | +228 (5.79) | -033 (0.84) |
| F | +321 (8.15) | -160 (4.06) | Y | +174 (4.42) | -151 (3.84) |
| G | +242 (6.15) | -265 (6.73) | Z | +065 (1.65) | -221 (5.61) |
| H | +130 (3.30) | -335 (8.51) | a | -065 (1.65) | -221 (5.61) |
| J | -000 (0.00) | -359 (9.12) | b | -174 (4.42) | -151 (3.84) |
| K | -130 (3.30) | -335 (8.51) | c | -228 (5.79) | -033 (0.84) |
| L | -242 (6.15) | -265 (6.73) | d | -209 (5.31) | +092 (2.41) |
| M | -321 (8.15) | -160 (4.06) | e | -124 (3.15) | +193 (4.90) |
| N | -357 (9.07) | -033 (0.84) | f | +000 (0.00) | +096 (2.44) |
| P | -345 (8.76) | +098 (2.49) | g | +096 (2.44) | +000 (0.00) |
| R | -286 (7.26) | +217 (5.51) | h | +000 (0.00) | -096 (2.44) |
| S | -189 (4.80) | +305 (7.75) | j | -096 (2.44) | +000 (0.00) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 19 | -32 | 32 | 20 | I | All | MS20054-32 |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal |
|-----|---------------|
| B | 33.91+0/-0.25 |
| ØC | 35.18+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D719K32SNL

| | | | |
|----------------|----------------------|---|------------------|
| A | 30-09-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | | Stainless Steel Receptacle 8D series | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | | WWW.SOURIAU.COM | |
| | | This document is the property of SOURIAU it must not be reproduced or communicated without permission | |
| FORMAT | SOURIAU DRG N° | | SHEET |
| A3 | 8D719K32SNL-C | | 2/2 |