



Features

- Epitaxial planar die construction
- Complimentary to MMBT2222A
- Ultra-small surface mount package

HF

Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-23

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBT2907A	SOT-23	3000 pcs / Tape & Reel	2F

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V _{CBO}	-60	V
Collector-Emitter Breakdown Voltage	V _{CEO}	-60	V
Emitter-Base Breakdown Voltage	V _{EBO}	-5	V
Collector Current (Continuous)	I _C	-0.6	A
Collector Current (Peak)	I _{CM}	-1.2	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	300	mW
Thermal Resistance (Junction-to-Ambient) *1	R _{θJA}	417	°C/W
Thermal Resistance (Junction-to-Case) *1	R _{θJC}	380	°C/W
Thermal Resistance (Junction-to-Lead) *1	R _{θJL}	350	°C/W
Ambient Temperature	T _A	-55 ~ +150	°C
Operating junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}$, $I_E = 0$	-60	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = -10\text{mA}$, $I_B = 0$	-60	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = -10\mu\text{A}$, $I_C = 0$	-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -50\text{V}$, $I_E = 0$	-	-	-10	nA
Collector Cut-off Current	I_{CEX}	$V_{CE} = -30\text{V}$, $V_{EB(OFF)} = -0.5\text{V}$	-	-	-50	nA
Base Cut-off Current	I_{BL}	$V_{CE} = -30\text{V}$, $V_{EB(OFF)} = -0.5\text{V}$	-	-	-50	nA
DC Current Gain	h_{FE}	$V_{CE} = -10\text{V}$, $I_C = -0.1\text{mA}$	75	-	-	-
		$V_{CE} = -10\text{V}$, $I_C = -1\text{mA}$	100	-	-	-
		$V_{CE} = -10\text{V}$, $I_C = -10\text{mA}$	100	-	-	-
		$V_{CE} = -10\text{V}$, $I_C = -150\text{mA}$	100	-	300	-
		$V_{CE} = -10\text{V}$, $I_C = -500\text{mA}$	50	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -500\text{mA}$, $I_B = -50\text{mA}$	-	-	-1.6	V
		$I_C = -150\text{mA}$, $I_B = -15\text{mA}$	-	-	-0.4	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -500\text{mA}$, $I_B = -50\text{mA}$	-	-	-2.6	V
		$I_C = -150\text{mA}$, $I_B = -15\text{mA}$	-	-	-1.3	V
Transition Frequency	f_T	$I_C = -50\text{mA}$, $V_{CE} = -20\text{V}$ $f = 100\text{MHz}$	200	-	-	MHz
Collector Output Capacitance	C_{OBO}	$V_{CB} = -10\text{V}$, $I_E = 0$, $f = 1\text{MHz}$	-	-	8	pF
Input Capacitance	C_{IBO}	$V_{EB} = -2\text{V}$, $I_C = 0$, $f = 1\text{MHz}$	-	-	30	pF
Delay Time	t_d	$V_{CC} = -30\text{V}$, $I_C = -150\text{mA}$ $I_{B1} = -15\text{mA}$	-	-	10	ns
Rise Time	t_r		-	-	40	ns
Storage Time	t_s	$V_{CC} = -6\text{V}$, $I_C = -150\text{mA}$	-	-	80	ns
Fall Time	t_f	$I_{B1} = I_{B2} = -15\text{mA}$	-	-	30	ns

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(on)}$ vs. I_C




Fig 5 I_C vs. V_{CE}




Fig 6 P_D vs. T_A





Fig 7 C_J vs. V_R


Package Outline Dimensions (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

Package Outline Dimensions (Unit: mm)

SOT-23



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.