

MESSRS.

SPECIFICATION FOR APPROVAL

承 認 书

Product	DYNAMIC SPEAKER
Part No.	HDK-241508EA-1P (RoHS)
Customer Approval	

Approved By	Checked By	Made By
王台平 JAN-02-2014	曹丽萍 JAN-02-2014	LILY JAN-02-2014

常 州 华 龙 电 子 有 限 公 司

DRAGONSTATE ELECTRONIC CORPORATION

中国江苏省常州市新区电子园新四路 36 号

Tel: +86-519-85110078. 86-519-85106698, Fax: +86-519-85101081

1. Specification

HDK-241508EA-1P (RoHS)

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 24×15 mm	
03	Rated Input Power	0.8W	
04	Max. Input Power	1.2W for 1 minute	
05	Impedance	8 ohm ± 15% at 1500Hz.	
06	Resonance Frequency (Fo)	750Hz ± 20% at Fo, 1V	
07	Sensitivity (S.P.L.)	90dB(0.1W/0.1m) ± 3 dB	at AVE 0.8K, 1.0K, 1.2K, 1.5KHz.
		96dB(0.8W / 0.1m) ± 3 dB	
08	Frequency Range	Fo - 20KHz	
09	Total Harmonics Distortion	Max 8 % at 1 KHz, 0.8W.	
10	Voice Coil	Diameter 8.5 mm	
11	Magnet	Rare earth permanent (Nd-Fe-B) magnet Φ 8.0 x 1.0 mm	
12	Weight	2.0g ± 0.2g	
13	Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.	
14	Operation Test	Must be normal at program source - 0.8W	
15	Buzz, Rattle, etc.	Should not be audible at 2.53V sine Wave between Fo to 20KHz	
16	Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.	
17	Terminal Strength	Capable of withstand 1kg load for 30 seconds without resulting in any damage or rejection.	
18	Temperature	Operating temperature: -20℃ to +60℃ Storage temperature: -30℃ to +70℃	

2-1. Test Condition

Standard

Temperature : 15 ~ 35℃

Relative humidity : 25% ~ 85%,

Atmospheric pressure : 860mbar to 1060mbar.

Basic

Temperature : $20 \pm 3^{\circ}\text{C}$

Relative humidity : 60% ~ 70%,

Atmospheric pressure : 860mbar to 1060mbar

2-2. Standard Test Fixture


1. Input Power : 0.8W (2.53V)

2. Zero Level : -dB


3. Mode : SPEAKER

4. potentiometer Range : 50dB

5. Sweep Time : 0.5sec




2-3. Frequency Response Curve 0.8W/10cm




Mode: SSR



3. Dimension






4. Reliability Test

Items.		Specifications
01	High temp. Test	Keep 96 hours at $+70^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and leave 3 hours in normal temperature and then check
02	Low temp. Test	Keep 96 hours at $-30^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and leave 3 hours in normal temperature and then check
03	Humidity test	Keep 96 hours at $+60^{\circ}\text{C} \pm 3^{\circ}\text{C}$ relative humidity 95% and leave 3 hours in normal temperature and then checked.
04	Temp./Humidity cycle	The part shall be subjected 5 cycles. One cycle shall be 12 hours and consist of; 
05	Thermal cycle test.	Low temperature: $-30^{\circ}\text{C} \pm 3^{\circ}\text{C}$, temperature: $+70^{\circ}\text{C} \pm 3^{\circ}\text{C}$, cycle: 1 hour/cycle each, and then keep 5 cycles in a room.
06	Vibration	10~200~10Hz sin-wave sweep 15min. 5G(constant) X, Y, Z 3 direction. 2 hours each, total 6 hours.
07	Fix drop test	Fix on jig. Then drop from 152cm height to the concrete floor X, y, z 6 direction. 5 times each, total 30 times.
08	Free drop test	Free drop from 100cm height to the concrete floor X, y, z 6 direction. 1 times each, total 6 times.
09	Rated Power test	Rated Power white noise is applied for 96 hours
10	Max Power test	Max power 1 min on - 2 min off 10 cycles.
11	Terminal strength test	Capable of withstand 1kg load for 30 seconds without resulting in any damage or rejection.
Criterion: After these test , the change of S.P.L shall be within ± 3 dB .		

Soldering Condition

Recommend using constant branding iron in 15 ~ 30W, and in temperature range $350 \pm 10^{\circ}\text{C}$.
 Soldering time not over 3 seconds.

5. Packing

REV NO.	REVISION NOTE	APPROVAL	DATE
	 Cover(320*220*5mm) Material: Paper		
	 Box(325*220*15mm) Epe(325*220*10) 100pcs Material: Paper+Epe		
	 Middle(320*220*120mm) 1000pcs(10*100pcs) Material: Paper+Epe		
	 Outer Box(490*360*350mm) 5000pcs(5*1000pcs) Material: Paper		
单位: mm			
TITLE: packing		DRAWN: Lily 2014/01/04	SCALE: 2:1 SHEET: 1 of 1
PART NO. 1 DWG NO. REV		DESIGNED: R&D OF D.S.	UNITS: mm
		CHECKED: Emily	TOLERANCE
		APPROVAL: Eric	20~11 ± 0.3 10~5 ± 0.2
		MATERIAL: ***	<4 ± 0.1
DS DRAGONSTATE ELECTRONIC CORPORATION			



6. History change record

[illegible]