



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DRC Housings



Connector System: **Wire-to-Wire**

Number of Positions: **70**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **5.49 mm [ .216 in ]**

Sealable: **Yes**

[All DEUTSCH DRC Housings \(112\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Contact Retainer

Configuration Features

Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	70
Number of Rows	5

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features

Cable Exit Angle	180°
------------------	------



Primary Product Color	Black
Connector & Keying Code	A

Contact Features

Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PPS GF
Centerline (Pitch)	5.49 mm[.216 in]

Dimensions

Connector Height	36.06 mm[1.421 in]
Product Width	103.99 mm[4.094 in]
Product Length	41.73 mm[1.643 in]
Row-to-Row Spacing	5.49 mm[.216 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94

Packaging Features

--	--



Packaging Quantity	50
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

DRC16-70SAE

Housing for Female Terminals, Wire-to-Wire, 70 Position, .216 in [5.49 mm]  
Centerline, Sealable, Black, Wire & Cable, Power & Signal, DEUTSCH DRC



TE Part # CAT-D799-CH8172  
DEUTSCH DRC Housings

TE Part # CAT-J67-DSCC16  
DEUTSCH Size 16 Crimp Contacts

TE Part # CAT-D48-ST273  
DEUTSCH Solid Contacts

TE Part # CAT-D48-SP729  
DEUTSCH Sealing Plugs

TE Part # DRC70-BT  
BOOT, 70P, 16SZ, PLG/REC, ST, BLK

TE Part # CAT-D799-H342  
DEUTSCH DRC Headers

TE Part # CAT-D799-B128  
DEUTSCH DRC Backshells

TE Part # 0411-336-1605  
EXT TOOL, SIZE 16, 16-20 AWG, E, DRK BLU

TE Part # 0515-006-7005  
PROTECT CVR, 70P, PLG, WHT, DRC16

TE Part # 0515-031-7005  
WIRE ROUTER, 70P, BLK, PLG

TE Part # 1062-14-0177  
SOC, SF, SIZE 16, 14-18, SN/SN

Also in the Series | DEUTSCH DRC

Automotive Housings(112)

Connector Backshells(6)


Connector Strain Relief(3)

Insertion & Extraction Tools(7)


PCB Headers & Receptacles(44)

Customers Also Bought







TE Part #2-1564414-1  
12POS,TAB 1.6X0.6,TAB HSG,ASSY




TE Part #DRC12-40PAE  
DEUTSCH DRC Housings




TE Part #HDP26-24-19SE-L017  
PLG, 19P, BLK, E, RNG, 12/16, S




TE Part #DT04-08PA-CE04  
REC, 8P, GRY, E, XCAP, A



TE Part #7-1579007-0  
EXTRACTION TOOL



TE Part #0528-006-7005  
BKSHL, 70P, BLK, PLG, ST, SIDEAB, NW 26



TE Part #0515-001-4005  
PROTECT CVR, 40P, PLG, WHT, DRC16

Documents

Product Drawings

PLG, 70P, BLK, E, A

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_DRC16-70SAE\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_DRC16-70SAE\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_DRC16-70SAE\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

Product Specifications

Engineering Report

English

Agency Approvals

UL Report

DRC16-70SAE

Housing for Female Terminals, Wire-to-Wire, 70 Position, .216 in [5.49 mm]  
Centerline, Sealable, Black, Wire & Cable, Power & Signal, DEUTSCH DRC



English