

REVISIONS REV ECO DESCRIPTION DATE BY APPR A1 RELEASE NEW DRAWING 12MAY20 IAN TOMMY MODIFY PRODUCT NAME 11AUG20 IAN TOMMY

(17 PLACES) 47.6 Ø50.8 -SIZE 12 CONTACTS 6 (4 PLACES)

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: SMOOTH RING ADAPTER (SRA); STANDARD DIA. WIRE SEAL.


3. SPECIFICATIONS:

- 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
- 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP06-24-21P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND WIRE RANGE:

| CONTACT SIZE | MIN. INSUL O.D. | MAX. INSUL O.D. | TYPICAL WIRE RANGE | CURRENT RATING |
|-----------------|----------------------|----------------------|---------------------------|-------------------|
| 12 | 3.43 mm (.134 in) | 4.32 mm (.170 in) | 10-14 AWG (6.0-2.0mm²) | 25 AMPS |
| 16 | 2.54 mm (.100 in) | 3.40 mm (.134 in) | 14-20 AWG (2.0-0.5mm²) | 13 AMPS |

7. RECEPTACLE IS SUPPLIED WITH DUST CAP.



RECOMMENDED PANEL MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM

| SMOOTH RING ADAPTER - GREEN | MIDI STETE CITY OF |
|-----------------------------|--------------------|
| | ۲ |

| | AUDF04-2 | 4-2 1311 | -SINA | REF:HDP24-24-21SN | | | | |
|--|------------|--|----------------------------------|--|--|-----------------|--------------|------|
| | PART N | NUMBER | | | DESCRIPTION | | | ITEM |
| QUANTITY | | MATERIALS LIST | | | | | | |
| UNLESS OTHER | | SIGN | NATURES | DATE | Λ m | nha | nol. | |
| All dimensions a Tolerances are a PL DEC ±0.30 | | DRAWN: | IAN.XIAO | 11AUG20 | Amphenol | | | |
| 2 PL DEC ±0.15 3 PL DEC ±0.08 | Angles ±1° | CHECKED: | ORION.LI | 12AUG20 | Sine System | ıs - www.ampher | nol-sine.com | |
| 3) Note reference | = <u>x</u> | ENGINEER: | | | 44724 Morley Drive | | 000 | |
| MATERIAL SPECIFICATIONS: APPROVAL: TOMMY.XI | | TOMMY.XIE | 13AUG20 | Clinton Township, MI 48036 | | | | |
| | | CUSTOMER: | | | RECEPT. | ,SIZE 24,21-S | SOCKET, | |
| | | | NG IS SUPPLIED N ONLY, DESIGN | | NORMAL SEAL, SRA, DURAMATE AHDP SERIES | | | |
| PROCESS SPECIFICATIONS: SPE SHO THE OFF | | SPECIFICATION SHOWN HERE THE AMPHEN OF REPRODU | | ORMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL | B C - AHDP04-24-21SN-SR | | | A2 |
| | | | RING VARIATION | 4S. | ALE:NONE DUF | RAMATE | SHEET 1 OF | 1 |

ΔHDP04-24-21SN-SRΔ

A Series™ - Contact Size 12 Options (Works with: AHD-6, ATP, ATHD, DuraMate and PanelMate Series)

| Machined Contacts, Sockets & Pins | | | | |
|-----------------------------------|--|------|-------|----------|
| Part Number | Description | Size | AWG | Туре |
| *AT60-204-12141-10 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Machined |
| *AT62-203-12141-10 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Machined |
| AT60-220-1231 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Machined |
| AT62-210-1231 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Machined |
| AT60-204-12141 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Machined |
| AT62-203-12141 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Machined |

^{*}Works with ATP Series only

| | • Smaller AWG fo | DiagnosticGrade™ Machined Contacts, Sockets & Pi or Diagnostic Applications • Gold-plated • Increased Matin | | es • Cost-e | effective |
|---|--------------------|--|------|-------------|-----------|
| | Part Number | Description | Size | AWG | Туре |
| Γ | 65-54749 | Male Contact - DiagnosticGrade™, Pin, Gold-plated | 12 | 20 | Machined |
| | AT62-210-1231-1820 | Female Contact - DiagnosticGrade™, Socket, Gold-plated | 12 | 20 | Machined |

| | Tooling - Machined Contacts | | | |
|-------------|--|--|--|--|
| Part Number | Description | | | |
| AUTK-12 | Hand Crimp Tool, Size 12 | | | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | | | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | | | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | | | |
| M300-25A | Hand Crimp Tool used with Crimp Locator MFX-3966, Size 12, 10AWG | | | |
| MFX-3966 | Contact Locator used with Hand Crimp Tool M300-25A, Size 12, 10AWG | | | |

| Cor | Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | |
|---------------|--|--|--|
| Part Number | Part Number Description | | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | | |
| AT11-337-1205 | Contact Removal Tool, Plastic, Size 12 | | |

| Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | | |
|--|------------------------------|--|--|
| Part Number | Part Number Description | | |
| A114017 | Sealing Plug, Size 12, White | | |

| | Stamped & Formed Contacts, Sockets & Pins | | | | | |
|--------------|---|------|-------|------------------|--|--|
| Part Number | Description | Size | AWG | Туре | | |
| AT60-12-0244 | Male Contact - Pin, Gold-plated | 12 | 10-12 | Stamped & Formed | | |
| AT62-12-0244 | Female Contact - Socket, Gold-plated | 12 | 10-12 | Stamped & Formed | | |
| AT60-12-0222 | Male Contact - Pin, Nickel-plated | 12 | 10-12 | Stamped & Formed | | |
| AT62-12-0222 | Female Contact - Socket, Nickel-plated | 12 | 10-12 | Stamped & Formed | | |
| AT60-12-0144 | Male Contact - Pin, Gold-plated | 12 | 12-14 | Stamped & Formed | | |
| AT62-12-0144 | Female Contact - Socket, Gold-plated | 12 | 12-14 | Stamped & Formed | | |
| AT60-12-0166 | Male Contact - Pin, Nickel-plated | 12 | 12-14 | Stamped & Formed | | |
| AT62-12-0166 | Female Contact - Socket, Nickel-plated | 12 | 12-14 | Stamped & Formed | | |

| | Tooling - Stamped & Formed Contacts | | |
|-------------|---|--|--|
| Part Number | Description | | |
| MFX-3973 | Crimp Die - Size 12 | | |
| MFX-3985 | Crimp Die - Svize 12, 10-12AWG -02XX Series | | |
| ATT-12-00 | Hand Crimp Tool - Size 12, 12AWG | | |
| ATT-12-01 | Hand Crimp Tool - Size 12, 10AWG | | |

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

| | Machined Contacts, Sockets & Pins | | | | |
|-------------------|--|------|-------|----------|--|
| Part Number | Description | Size | AWG | Туре | |
| AT60-215-1631 | Male Contact - Pin, Gold-plated | 16 | 14 | Machined | |
| AT62-209-1631 | Female Contact - Socket, Gold-plated | 16 | 14 | Machined | |
| AT60-215-16141 | Male Contact - Pin, Nickel-plated | 16 | 14 | Machined | |
| AT62-209-16141 | Female Contact - Socket, Nickel-plated | 16 | 14 | Machined | |
| AT60-202-1631 | Male Contact - Pin, Gold-plated | 16 | 16-20 | Machined | |
| AT62-201-1631 | Female Contact - Socket, Gold-plated | 16 | 16-20 | Machined | |
| AT60-202-16141 | Male Contact - Pin, Nickel-plated | 16 | 16-20 | Machined | |
| AT62-201-16141 | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined | |
| AT60-202-1631-22 | Male Contact - Pin, Gold-plated | 16 | 22-24 | Machined | |
| AT62-201-1631-22 | Female Contact - Socket, Gold-plated | 16 | 22-24 | Machined | |
| AT60-202-16141-22 | Male Contact - Pin, Nickel-plated | 16 | 22-24 | Machined | |
| AT62-201-16141-22 | Female Contact - Socket, Nickel-plated | 16 | 22-24 | Machined | |

| Tooling - Machined Contacts | | | |
|-----------------------------|---|--|--|
| Part Number | Description | | |
| AUTK-16 | Hand Crimp Tool, Size 16 | | |
| AUTK-100 | Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20 | | |
| CA-5D12 | Universal Hand Crimp Tool, Size 12/16/20 | | |
| CA-5E12 | Pneumatic Crimp Tool, Size 12/16/20 | | |

| Contact Removal Tools (For both Machined or Stamped & Formed Contacts) | | | | |
|--|--|--|--|--|
| Part Number | Description | | | |
| ATRT-100 | Contact and Wedgelock Extraction Tool | | | |
| AT11-310-1605 | Contact Removal Tool, Plastic, Size 16 | | | |

| Sealing Plugs (For both Machined or Stamped & Formed Contacts) | | | | |
|--|---|--|--|--|
| Part Number | Description | | | |
| A114017 | Sealing Plug, Size 16, White | | | |
| A114017-SR | Sealing Plug, Size 16, SR01 Series, Black | | | |
| AT13-217-1605 | Locking Sealing Plug, Size 16, Grey | | | |
| AT13-217-1605-SR | Locking Sealing Plug, Size 16, SR01 Series, Red | | | |

| Stamped & Formed Contacts, Sockets & Pins | | | | | |
|---|---|---|---|--|--|
| Description | Size | AWG | Туре | | |
| Male Contact - Pin, Nickel-plated | 16 | 14-18 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 14-18 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 14-18 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 14-18 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 16-18 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 16-18 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Tin-plated | 16 | 16-20 | Stamped & Formed | | |
| Female Contact - Socket, Tin-plated | 16 | 16-20 | Stamped & Formed | | |
| Male Contact - Pin, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |
| Female Contact - Socket, Nickel-plated | 16 | 20-22 | Stamped & Formed | | |
| Male Contact - Pin, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| Female Contact - Socket, Gold-plated | 16 | 20-22 | Stamped & Formed | | |
| | Description Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Tin-plated Female Contact - Socket, Tin-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Gold-plated | DescriptionSizeMale Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Nickel-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Pin, Gold-plated16Male Contact - Pin, Mickel-plated16Female Contact - Socket, Gold-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Tin-plated16Female Contact - Pin, Tin-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16 | DescriptionSizeAWGMale Contact - Pin, Nickel-plated1614-18Female Contact - Socket, Nickel-plated1614-18Male Contact - Pin, Gold-plated1614-18Female Contact - Socket, Gold-plated1614-18Male Contact - Pin, Nickel-plated1616-18Female Contact - Socket, Nickel-plated1616-18Male Contact - Pin, Gold-plated1616-18Female Contact - Socket, Gold-plated1616-18Male Contact - Pin, Nickel-plated1616-20Female Contact - Socket, Nickel-plated1616-20Male Contact - Pin, Gold-plated1616-20Female Contact - Socket, Gold-plated1616-20Male Contact - Pin, Tin-plated1616-20Female Contact - Pin, Tin-plated1616-20Male Contact - Pin, Nickel-plated1616-20Male Contact - Socket, Tin-plated1616-20Male Contact - Pin, Nickel-plated1620-22Female Contact - Socket, Nickel-plated1620-22Male Contact - Pin, Gold-plated1620-22 | | |

| Tooling - Stamped & Formed Contacts | | |
|-------------------------------------|-------------------------------------|--|
| MFX-3950 | Crimp Die - Size 16, 18-20AWG | |
| MFX-3953 | Crimp Die - Size 16, 16-18AWG | |
| MFX-3975 | Crimp Die - Size 16, 14-16AWG | |
| MFX-3990 | Crimp Die - Size 16, 20-22AWG | |
| ATT-16-00 | Hand Crimp Tool - Size 16, 14-16AWG | |
| ATT-16-01 | Hand Crimp Tool - Size 16, 18-20AWG | |
| ATT-1612-03 | Hand Crimp Tool - Size 16, 20-22AWG | |