APPLICAE	BLE STAN	DARD									
	OPERATING	E DANCE	55 °C TO 95 °	°C (1)		RAGE	DE DANK	<u></u>	10 °C TO 60 °	C (2)	
RATING	TEMPERATURE RANGE				TEMPERATING OPERATING				-10 °C TO 60 °C (2)		
	VOLTAGE CURRENT		100 V AC		RANG				40 % TO 80 %		
			0.5 A			NGE 40 % TO 70 %			(2)		
			SPEC	CIFICA	TION	S					
ITI	EM		TEST METHOD	)			RE	QUI	REMENTS	QT	A.
CONSTRU											
	KAMINATION		LY AND BY MEASURING IN	NSTRUME	NT.	ACCOF	RDING T	O DR	AWING.	×	×
MARKING ELECTRIC	, CHVBVC.		MED VISUALLY.							×	×
ELECTRIC CHARACT CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).				40 mΩ MAX.				×	Τ_
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				50 mΩ MAX .				×	-
INSULATION RESISTANCE		250 V DC				100 MΩ MIN.				×	-
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.					_
	CAL CHAR								00.0111111	×	_
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE: 88.2 N MAX. WITHDRAWAL FORCE: 9.8 N MIN.					-
MECHANICAL OPERATION		100 TIMES INSERTIONS AND EXTRACTIONS.				CONTACT RESISTANCE: 50 mΩ MAX.     NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-
VIBRATION		FREQUENCY 10 TO 55 Hz, AMPLITUDE: 1.5 mm,				① NO ELECTRICAL DISCONTINUITY OF 1 μs.				×	_
SHOCK		AT 2 h FOR 3 DIRECTIONS.  490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	-
ENVIRONI	MENTAL C		TERISTICS								
DAMP HEAT			DAT 40±2 °C, 90 ~ 95	5 %, 96	h.	① COI	NTACT F	RESIS	TANCE: 50 mΩ MAX.	×	T -
(STEADY STATE) RAPID CHANGE OF		TEMPERATURE-55→+15~+35→ +85→+15~+35°C			. 05-0	_			SISTANCE:100 MΩ MIN.	×	
TEMPERATURE		TIME $30 \rightarrow MAX 5 \rightarrow 30 \rightarrow MAX 5 min$ UNDER 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					-
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				$\bigcirc$ CONTACT RESISTANCE: 50 m $\Omega$ MAX. $\bigcirc$ NO HEAVY CORROSION.				×	-
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)								×	-
RESISTANCE TO		1) REFLOW SOLDERING : 250 °C MAX,				NO DEFORMATION OF CASE OF					-
SOLDERING HEAT		: 220 °C MIN, FOR 60 s				EXCESSIVE LOOSENESS OF THE TERMINALS.					
		2) SOLDERING IRONS : 360 °C,									-
SOLDERABIL	ITV	801055	FOR	5 s		A NIEVA	/ LINUE O	DN4 O	DATING OF SOLDED		
OOLDENADIEH		SOLDERED AT SOLDER TEMPERATURE, 240±3°C, FOR IMMERSION DURATION, 3 s.				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.				×	
COUN	T D	 ESCRIPTI	ON OF REVISIONS		DESIG	SNED			CHECKED		\ \TE
$ \mathcal{A} $										08. 01. 2 <sup>-</sup> 08. 01. 2 <sup>-</sup>	
			NDICATES A LONG-TERM STORAGE STATE ED PRODUCT BEFORE THE BOARD MOUNTED.			APPROVED CHECKED DESIGNED			HS. OKAWA HS. OZAWA		
								NED	SY. KAMIGA		01.2
Unless otl	nerwise spe	ecified, r	ed, refer to MIL-STD-1344.			DRAWN			SY. KAMIGA	<u> </u>	
Note QT:Qu	alification Tes	t AT:Assı	AT:Assurance Test X:Applicable Test			RAWING NO.			ELC4-084986-23		
HRS.	SI	SPECIFICATION SHEET			PART NO.		FX6-100S-0. 8SV2 (93)			3)	
117	HIR	OSE EI	LECTRIC CO., LTD.		CODE	NO.	CL	_576	-0128-4-93	$\triangle$	1/