APPLICAI	BLE STAN	DARD										
	OPERATING	E DANCE	-55 °C TO 85 °	oc (1)		RAGE		<u>,_</u>	-10 °C TO 60 °	C (2)		
RATING	TEMPERATURE RANGE				OPE	RATING	TURE RANGE NG HUMIDITY					
	VOLTAGE		100 V AC			GE RAGE HUMIDITY		+	40 % TO 80 %			
	CURRENT		0.5 A RA			IGE 40			40 % TO 70 %) % TO 70 % ⁽²⁾		
			SPEC	IFICA	MOIT	S						
ITEM			TEST METHOD			REQUIREMENTS			QT	Α		
CONSTRU												
	XAMINATION		Y AND BY MEASURING IN	ISTRUME	ENT.	ACCO	RDING T	O DR	AWING.	×	×	
MARKING	2 0114 D 4 0		MED VISUALLY.							×	×	
	CHARACTESISTANCE		(DC OR 1000 Hz).					40 m	ηΩ MAX.	×	Τ_	
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				50 mΩ MAX .				×	_	
INSULATION		250 V DC				100 MΩ MIN.				×	†-	
RESISTANCE VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×	+-	
MECHANI	CAL CHAR	ACTERI	STICS									
MECHANICAL OPERATION		100 TIMES INSERTIONS AND EXTRACTIONS.				CONTACT RESISTANCE: 50 mΩ MAX. NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	_	
VIBRATION		FREQUENCY 10 TO 55 Hz, AMPLITUDE: 1.5 mm, AT 2 h FOR 3 DIRECTIONS.				 NO ELECTRICAL DISCONTINUITY OF μs. NO DAMAGE, CRACK AND LOOSENESS PARTS. 				×	-	
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.								×	-	
FN∖/IR∩N	MENTAL C		TERISTICS	IONO.								
DAMP HEAT			DAT 40±2°C, 90 ~ 95	5 %. 96 l	h.	① CO	NTACT F	RESIS	TANCE: 50 mΩ MAX.	×	Τ-	
(STEADY STATE) RAPID CHANGE OF		TEMPERATURE-55→+15~+35→ +85→+15~+35°C				2 INSULATION RESISTANCE:100 M Ω MIN. 3 NO DAMAGE, CRACK AND LOOSENESS				×	-	
TEMPERATURE		TIME $30 \rightarrow MAX 5 \rightarrow 30 \rightarrow MAX 5 min$ UNDER 5 CYCLES.				OF PARTS.						
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 50 m Ω MAX. ② NO HEAVY CORROSION.				×	_	
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)								×	-	
RESISTANCE TO SOLDERING HEAT		1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				×	-	
		2) SOLDE	RING IRONS : 360 °C,			I LI (IVII	IVALO.			×	-	
SOLDERABILITY		FOR 5 s SOLDERED AT SOLDER TEMPERATURE,				A NEW UNIFORM COATING OF SOLDER					+-	
		240±3°C, FOR IMMERSION DURATION, 3 s.				SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.						
COUN	T D	ESCRIPTION	DN OF REVISIONS		DESIG	GNED			CHECKED		DATE	
DEMARK (1) TEMPER AT: ::	NI LIDED WILLEN ENERGIZES	NEPGIZED			 	VE -	Ho orawa	00 -	.7 ^		
			NCLUDED WHEN ENERGIZED. ATES A LONG-TERM STORAGE STATE ODUCT BEFORE THE BOARD MOUNTED.			APPROVED CHECKED DESIGNED		-	HS. OKAWA HT. YAMAGUCHI	08. C		
								NED			7. 2	
Unless ot	herwise spe	ecified, re	refer to MIL-STD-1344.			DRAWN		VN	HK. SUNADOR I	+		
	•	rance Test X:Applicable T				IG NO.			ELC4-084966-22			
									(6-40P-0. 8SV1 (92)			
HS.						NO.	CL	576	-0023-6-92	\wedge	1/1	
FORM HD0011-					CODE	. 110.	UL		3020 0 32	. <u>- </u>	.,	