


TOSHIBA Bipolar Linear Integrated Circuit Silicon Monolithic

TA48L018F, TA48L02F, TA48L025F, TA48L03F, TA48L033F, TA48L05F

1.8 V, 2 V, 2.5 V, 3 V, 3.3 V, 5 V

Three-Terminal Low Dropout Voltage Regulator with Output Current of 0.15 A

The TA48L**F series consists of fixed-positive-output, low-dropout regulators with an output current of 0.15 A (max) that utilize V-PNP transistors for the output stage. In response to the need for low-voltage and low-power dissipation devices for use in consumer electronics and industrial appliances, the series offers devices with low output voltages: 1.8 V, 2 V, 2.5 V, 3 V, 3.3 V, 5 V.




Weight: 0.05 g (typ.)

Features

- Maximum output current: 0.15 A
- Output voltage accuracy: $V_{OUT} \pm 3\%$ ($@T_j = 25^\circ\text{C}$)
- Low standby current: 400 μA (typ.) ($@I_{OUT} = 0\text{ A}$)
- Low-dropout voltage: $V_D = 0.5\text{ V}$ (max) ($@I_{OUT} = 100\text{ mA}$)
- Protection function: Overcurrent/Thermal shutdown
- Package type: PW-Mini (SOT-89) package

Pin Assignment / Marking



Note 2	Part No. (or abbreviation code)	Part No.
	AI	TA48L018F
	BI	TA48L02F
	CI	TA48L025F
	DI	TA48L03F
	EI	TA48L033F
	FI	TA48L05F

Note 1: A line beside a Lot No. identifies the indication of product Labels.

Without a line: $[[\text{Pb}]]/\text{INCLUDES} > \text{MCV}$

With a line: $[[\text{G}]]/\text{RoHS COMPATIBLE}$ or $[[\text{G}]]/\text{RoHS} [[\text{Pb}]]$

Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. The RoHS is the Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.


The product(s) in this document ("Product") contain functions intended to protect the Product from temporary small overloads such as minor short-term overcurrent or overheating. The protective functions do not necessarily protect Product under all circumstances. When incorporating Product into your system, please design the system (1) to avoid such overloads upon the Product, and (2) to shut down or otherwise relieve the Product of such overload conditions immediately upon occurrence. For details, please refer to the notes appearing below in this document and other documents referenced in this document.

How to Order

Product No.	Package	Packing Type and Unit for Orders
TA48L**F(F)	PW-Mini (SOT-89) Surface-mount package	On cut tape (TE12L,F): 100 pcs/tape section
TA48L**F (TE12L,F)		Embossed tape: 1000 pcs/tape

Note3: The “**” in each pro-forma product name is replaced with the output voltage of each product.

Block Diagram



Absolute Maximum Ratings (Ta = 25°C)

Characteristics	Symbol	Rating	Unit
Input voltage	V_{IN}	16	V
Output current	I_{OUT}	0.15	A
Operating temperature	T_{opr}	-40 to 85	°C
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55 to 150	°C
Power dissipation	P_D	0.5	W
Thermal resistance (Junction to ambient)	$R_{th(j-a)}$	250	°C/W

Note 4: External current and voltage (including negative voltage) should not be applied to pins not specified.

Note 5: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Protection Function (reference)

Characteristics	Symbol	Test Condition	Min	Typ.	Max	Unit
Thermal shutdown	$T_{SD} (T_j)$	—	—	160	—	°C
Peak circuit current	I_{PEAK}	$V_{IN} = V_{OUT} + 2 \text{ V}$, $T_j = 25^\circ\text{C}$	—	0.27	—	A
Short circuit current	I_{SC}	$V_{IN} = V_{OUT} + 2 \text{ V}$, $T_j = 25^\circ\text{C}$	—	0.27	—	A

Note 6: Various protection functions are not necessary guarantee of operating ratings below the absolute maximum ratings. Ensure that the devices operate within the limits of the maximum rating when in actual use.

Not Recommended
for New Design

TA48L018F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)

Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 3.8 V, I _{OUT} = 40 mA	1.746	1.8	1.854	V
		2.8 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	1.71	1.8	1.89	
Line regulation	Reg · line	2.8 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 3.8 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	40	mV
Quiescent current	I _B	2.8 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		2.8 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 2.1 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 2.1 V, I _{OUT} = 100 mA	—	5	20	
Output noise voltage	V _{NO}	V _{IN} = 3.8 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	45	—	μV _{rms}
Ripple rejection	R.R.	2.8 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	54	72	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.28	0.4	V
		I _{OUT} = 100 mA	—	0.32	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 3.8 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.3	—	mV/°C

TA48L02F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)

Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 4.0 V, I _{OUT} = 40 mA	1.94	2.0	2.06	V
		3.0 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	1.90	2.0	2.10	
Line regulation	Reg · line	3.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 4.0 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	40	mV
Quiescent current	I _B	3.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		3.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 2.1 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 2.1 V, I _{OUT} = 100 mA	—	5	20	
Output noise voltage	V _{NO}	V _{IN} = 4.0 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	55	—	μV _{rms}
Ripple rejection	R.R.	3.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	52	70	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.2	0.35	V
		I _{OUT} = 100 mA	—	0.3	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 4.0 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.35	—	mV/°C

TA48L025F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)

Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 4.5 V, I _{OUT} = 40 mA	2.425	2.5	2.575	V
		3.5 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	2.375	2.5	2.625	
Line regulation	Reg · line	3.5 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 4.5 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	40	mV
Quiescent current	I _B	3.5 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		3.5 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 2.4 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 2.4 V, I _{OUT} = 100 mA	—	7	20	
Output noise voltage	V _{NO}	V _{IN} = 4.5 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	65	—	μVrms
Ripple rejection	R.R.	3.5 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	52	70	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.16	0.35	V
		I _{OUT} = 100 mA	—	0.27	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 4.5 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.45	—	mV/°C

TA48L03F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)

Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 5.0 V, I _{OUT} = 40 mA	2.91	3.0	3.09	V
		4.0 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	2.85	3.0	3.15	
Line regulation	Reg · line	4.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 5.0 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	40	mV
Quiescent current	I _B	4.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		4.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 2.8 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 2.8 V, I _{OUT} = 100 mA	—	7	20	
Output noise voltage	V _{NO}	V _{IN} = 5.0 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	80	—	μVrms
Ripple rejection	R.R.	4.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	50	68	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.16	0.35	V
		I _{OUT} = 100 mA	—	0.27	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 5 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.5	—	mV/°C

TA48L033F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)

Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 5.3 V, I _{OUT} = 40 mA	3.2	3.3	3.4	V
		4.3 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	3.135	3.3	3.465	
Line regulation	Reg · line	4.3 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 5.3 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	40	mV
Quiescent current	I _B	4.3 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		4.3 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 3.0 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 3.0 V, I _{OUT} = 100 mA	—	7	20	
Output noise voltage	V _{NO}	V _{IN} = 5.3 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	85	—	μVrms
Ripple rejection	R.R.	4.3 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	50	68	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.16	0.35	V
		I _{OUT} = 100 mA	—	0.27	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 5.3 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.55	—	mV/°C

TA48L05F
Electrical Characteristics

 (C_{IN} = 0.33 μF, C_{OUT} = 3.3 μF, T_j = 25°C, unless otherwise specified)


Characteristics	Symbol	Test Conditions	Min	Typ.	Max	Unit
Output voltage	V _{OUT}	V _{IN} = 7.0 V, I _{OUT} = 40 mA	4.85	5.0	5.15	V
		6.0 V ≤ V _{IN} ≤ 12 V, 5 mA ≤ I _{OUT} ≤ 100 mA, 0°C ≤ T _j ≤ 125°C	4.75	5.0	5.25	
Line regulation	Reg · line	6.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA	—	2	20	mV
Load regulation	Reg · load	V _{IN} = 7.0 V, 5 mA ≤ I _{OUT} ≤ 150 mA	—	18	45	mV
Quiescent current	I _B	6.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 0 A	—	0.4	0.8	mA
		6.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 100 mA	—	1	5	
Starting quiescent current	I _{Bstart}	V _{IN} = 4.5 V, I _{OUT} = 0 A	—	0.5	1.5	mA
		V _{IN} = 4.5 V, I _{OUT} = 100 mA	—	7	20	
Output noise voltage	V _{NO}	V _{IN} = 7.0 V, I _{OUT} = 40 mA, 10 Hz ≤ f ≤ 100 kHz	—	135	—	μVrms
Ripple rejection	R.R.	6.0 V ≤ V _{IN} ≤ 12 V, I _{OUT} = 40 mA, f = 120 Hz	50	64	—	dB
Dropout voltage	V _D	I _{OUT} = 40 mA	—	0.16	0.35	V
		I _{OUT} = 100 mA	—	0.27	0.5	
Average temperature coefficient of output voltage	T _{CV0}	V _{IN} = 7.0 V, I _{OUT} = 5 mA, 0°C ≤ T _j ≤ 125°C	—	0.85	—	mV/°C

Electrical Characteristics for All Products

Generally, the characteristics of power supply ICs change according to temperature fluctuations.

The specification $T_j = 25^\circ\text{C}$ is based on a state where temperature increase has no effect (assuming no fluctuation in the characteristics) as ascertained by pulse tests.

Application Circuit Example



Be sure to connect a capacitor near the input terminal and output terminal between both terminals and GND.

The capacitances should be determined experimentally. In particular, adequate investigation should be made so that there is no problem even in high or low temperatures.

Usage Precautions

- Low voltage







Do not apply voltage to the Product that is lower than the minimum operating voltage, or the Product's protective functions will not operate properly and the Product may be permanently damaged.







- Overcurrent Protection

The overcurrent protection circuits in the Product are designed to temporarily protect Product from minor overcurrent of brief duration. When the overcurrent protective function in the Product activates, immediately cease application of overcurrent to Product. Improper usage of Product, such as application of current to Product exceeding the absolute maximum ratings, could cause the overcurrent protection circuit not to operate properly and/or damage Product permanently even before the protection circuit starts to operate.

- Overheating Protection

The thermal shutdown circuits in the Product are designed to temporarily protect Product from minor overheating of brief duration. When the overheating protective function in the Product activates, immediately correct the overheating situation. Improper usage of Product, such as the application of heat to Product exceeding the absolute maximum ratings, could cause the overheating protection circuit not to operate properly and/or damage Product permanently even before the protection circuit starts to operate.






Package Dimensions

HSOP3-P-1.50

Unit : mm



Weight: 0.05 g (typ.)

RESTRICTIONS ON PRODUCT USE

- Toshiba Corporation, and its subsidiaries and affiliates (collectively "TOSHIBA"), reserve the right to make changes to the information in this document, and related hardware, software and systems (collectively "Product") without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- Product is intended for use in general electronics applications (e.g., computers, personal equipment, office equipment, measuring equipment, industrial robots and home electronics appliances) or for specific applications as expressly stated in this document. Product is neither intended nor warranted for use in equipment or systems that require extraordinarily high levels of quality and/or reliability and/or a malfunction or failure of which may cause loss of human life, bodily injury, serious property damage or serious public impact ("Unintended Use"). Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. Do not use Product for Unintended Use unless specifically permitted in this document.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. TOSHIBA assumes no liability for damages or losses occurring as a result of noncompliance with applicable laws and regulations.