


- 技术要求1、插入力: 5~8N(0.3~3.0kgf)
 2、拔出力: 5~8N(0.3~3.0kgf)
 3、接触电阻: <math><30\text{m}</math>
 4、绝缘电阻: >100M DC 500V
 5、耐电压: AC 500V 1min无飞弧及击穿
 6、寿命: 10000 10~20次/min
 7、额定负载: DC 12V 3A
 8、适用温度范围: -25~85

序号	名称	材料	镀层/颜色	备注
1	平片	黄铜 0.35	银	
2	弹片	磷铜 0.3	银	
3	弯钩	黄铜 0.3	银	
4	圆针	黄铜 2.0	铜锡	
5	塑料盖	PPA	黑	
6	塑料座	PPA	黑	



DC-050-XX

中心针直径 (mm) : 20 : 2.0 , 25 : 2.5

DESIGNED		CHECKED		APPROVAL		DRAWING NUMBER		DATE		REV.		SCALE	
Mikey		Tom		Jerry		PART NAME		DC-050-XX		UNLESS OTHERWISE SPECIFIED, TOLERANCE:		X. ±0.25 X.x ±0.20 X.xx ±0.15 ANGULAR ±3°	
ECN BO.		new		2015/5/3		A		DESCRIPTION.		REV.		SCALE: 3:1	
DESIGNED		CHECKED		APPROVAL		DRAWING NUMBER		DATE		REV.		SCALE: 1/2	
Mikey		Tom		Jerry		PART NAME		DC-050-XX		UNLESS OTHERWISE SPECIFIED, TOLERANCE:		SCALE: 3:1	
						MODEL NAME		DC-050-XX		UNLESS OTHERWISE SPECIFIED, TOLERANCE:		SCALE: 3:1	
						3RD ANGLE PROJ		HanElectricity Co.,LTD		FILE.NO.			

瀚源