

Specification Sheet

Part Number: TAG10L-105

Laser printable self-laminating polyester has a smooth surface, allowing for the highest resolution and print contrast.

The material is 1.0 mil thick, allowing it to conform around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.



Laser Tag Label, Self-Laminating, 2.0" x .75" x 2.25", 16 Per Sheet, PET, White, 1000/pkg

Article Number 594-10105

Type TAG10L

Color White (WH)

Quantity Per pack

Product Description HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using a laser printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.

Short Description Laser Tag Label, Self-Laminating, 2.0" x .75" x 2.25", 16 Per Sheet, PET, White, 1000/pkg

| | |
|---------------------------------|----------------------------------|
| Global Part Name | TAG10L-105-WH |
| Width W (Imperial) | 2.0 |
| Width W (Metric) | 50.8 |
| Bundle Diameter Min (Imperial) | 0.25 |
| Bundle Diameter Min (Metric) | 6.35 |
| Bundle Diameter Max (Imperial) | 0.47 |
| Bundle Diameter Max (Metric) | 11.94 |
| Thickness T (Metric) | 35.0 |
| Width of Liner (Metric) | 215.00 |
| Width of Liner (Imperial) | 8.5 |
| Outside Diameter Max (Imperial) | 0.24 |
| Outside Diameter Min (Metric) | 6.1 |
| Outside Diameter Min (Imperial) | 0.24 |
| Outside Diameter Max (Metric) | 12.10 |
| Material | Type 105, Polyester, white (105) |

| | |
|--------------------------------|-----------------------------------|
| Material Shortcut | 105 |
| Adhesive | Acrylic |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +300°F (-40°C to +149°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3919905060 |
| Labels per Column | 4 |
| Labels per Row | 4 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin.
(www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)