

Specification Sheet

Part Number: 300-73611



Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.

Low shrink temperature gives excellent physical and electrical performance.

Available in multiple diameters and lengths offering several options to fit specific needs.

Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, 2.0" Supp/1.0" Recov Dia, PO-X, Black, 100ft/reel

Article Number 300-73611

Type TCN20-50.8/25.4

Color Black (BK)

Quantity Per box

Product Description

TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0" (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.

Short Description Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, 2.0" Supp/1.0" Recov Dia, PO-X, Black, 100ft/reel

Global Part Name

TCN20-50.8/25.4-PO-X-BK

Length L (Imperial) 100.0

Length L (Metric) 30.5

Variant Thin-Wall

Nominal Diameter (Imperial) 2

Nominal Diameter (Metric) 50.8

Wall Thickness WT (Imperial) 0.045

Wall Thickness WT (Metric) 1.15

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

Flammability UL 224 VW-1

Halogen Free No

UV Resistant (Yes/No) No

Operating Temperature -67°F to +257°F (-55°C to +125°C)

Reach Compliant (Article 33) Yes

ROHS Compliant	Yes
Certification/Specification	UL 224 125 °C 600V VW-1 CSA C22.2 no. 198.1-06 DIN 75200 (09/1980)
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	30
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)