



REV.	DESCRIPTION	ECN NO.	NAME	DATE

Part No	Pin	A	B
WF-1A254A2P	2	2.50	7.50
WF-1A254A3P	3	5.00	10.00
WF-1A254A4P	4	7.50	12.50
WF-1A254A5P	5	10.00	15.00
WF-1A254A6P	6	12.50	17.50
WF-1A254A7P	7	15.00	20.00
WF-1A254A8P	8	17.50	22.50
WF-1A254A9P	9	20.00	25.00
WF-1A254A10P	10	22.50	27.50
WF-1A254A11P	11	25.00	30.00
WF-1A254A12P	12	27.50	32.50
WF-1A254A13P	13	30.00	35.00
WF-1A254A14P	14	32.50	37.50
WF-1A254A15P	15	35.00	40.00
WF-1A254A16P	16	37.50	42.50
WF-1A254A17P	17	40.00	45.00
WF-1A254A18P	18	42.50	47.50
WF-1A254A19P	19	45.00	50.00
WF-1A254A20P	20	47.50	52.50

- 技术要求:
1. 塑件材料: PA66 (UL-94V-0)
 2. 接触件: 黄铜镀锡
 3. 接触电阻: $\leq 10m\Omega$
 4. 绝缘电阻: $\geq 100M\Omega$
 5. 额定电压: 250V AC DC
 6. 额定电流: 2.0A AC DC
 7. 耐压: 能承受 1000V AC/Minute
 8. 工作温度: $-25^{\circ} \sim +85^{\circ}$
 9. 可焊性试验: 浸锡面积 $> 95\%$ 温度 235 , 时间 2.5 ± 0.5 秒
 10. 铅和镉等六大有害物质含量要符合环保要求。

2	Contact	Brass	n*1	电镀(锡): 整个表面镀底镍 30u"MIN, 再镀锡 80u"MIN.
1	Wafer	PA66(UL94V-0)	1	本色
序号	名称	材料	数量	附注

GENERAL TOLERANCE		DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD				
DIM.	TOL.	TITLE: WAFER XH2.54MM 直转				
X		DWG. NO.: WF-1A254ANP		DRAWN: MAX		
X.X	± 0.30	PART NO.: WF-1A254ANP		CHECKED: ELLA		
X.XX	± 0.25	UNIT: mm		SCALE: none	SHEET: 1 of 1	APPROVED: WILL
X.XXX	± 0.15	DWG. SIZE: A4	LAYER: bxconn			
GENERAL ANGLE: $\pm 3^{\circ}$						

SUGGESTED PCB LAYOUT
(COMPONENT SIDE)