



Reverse Voltage - 200 V
Forward Current - 15.0A

TO-277B



Features

- Trench MOS Schottky technology
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

MECHANICAL DATA

- Case: TO-277B
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.003 ounce, 0.092 grams

Absolute Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

Parameter	Symbols	SP15200L	Units
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	200	V
Maximum RMS voltage	V_{RMS}	140	V
Maximum DC Blocking Voltage	V_{DC}	200	V
Maximum Average Forward Rectified Current	$I_{F(AV)}$	15.0	A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	250	A
Max Instantaneous Forward Voltage at 15.0 A	V_F	0.90	V
Maximum DC Reverse Current $T_a = 25^{\circ}C$ at Rated DC Reverse Voltage $T_a = 100^{\circ}C$	I_R	20 15	uA mA
Typical Thermal Resistance ⁽¹⁾	$R_{\theta JA}$ $R_{\theta JC}$	65 15	$^{\circ}C/W$
Operating Junction Temperature Range	T_j	-55 ~ +150	$^{\circ}C$
Storage Temperature Range	T_{stg}	-55 ~ +150	$^{\circ}C$

(1) Polyimide PCB, 2oz. Copper. Cathode pad dimensions 18.8mm x 14.4mm. Anode pad dimensions 5.6mm x 14.4mm

Typical Characteristics

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic







Fig.4 Maximum Non-Repetitive Peak Forward Surge Current



PACKAGE OUTLINE Dimensions in millimeters and (inches)



The recommended mounting pad size



Marking

Type number	Marking code
SP15200L	SP15200L