

Part Number: 1200790246

Product Description: Ultra-Lock (M12) Single-Ended Cordset, 5 Poles, Male (90°) to Pigtail, 22 AWG, Yellow PVC Cable, 5.0m (16.40')

Length

Status: Active

Engineering Number: W05007A09M050

Series Number: 120079

**Product Category:** Circular Industrial

Cordsets

#### **Documents & Resources**

**Drawings** 

Drawing 1200790246\_sd.pdf

## **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | Not Relevant                                      |
| EU ELV             | Compliant with Exemption 3 per 2000/53/EC         |
| Low-Halogen Status | Not Relevant                                      |
| REACH SVHC         | Contains Lead per D(2023)3788-DC<br>(14 Jun 2023) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **EU RoHS Certificate of Compliance**

## **Part Details**

## General

| Status         | Active   |
|----------------|--|
| Category       | Circular Industrial Cordsets   |
| Series         | 120079   |
| Description    | Ultra-Lock (M12) Single-Ended<br>Cordset, 5 Poles, Male (90°) to<br>Pigtail, 22 AWG, Yellow PVC Cable,<br>5.0m (16.40') Length |
| IP Rating      | IP69K  |
| Product Family | Brad Ultra-Lock Connection System  |
| Product Name   | Ultra-Lock (M12)   |
| Protocol       | EtherNet   |
| Region         | America  |
| Туре           | Single Ended   |
| UPC            | 78678884793  |

# Agency

| CSA | LR6837 |
|-----|--------|
|     |        |
|     | ( SA   |

## Electrical

| Current - Maximum per Contact | 4.0A       |
|-------------------------------|------------|
| Voltage - Maximum             | 250V AC/DC |

# Physical

| Cable Diameter          | 5.72mm (.225")   |
|-------------------------|------------------|
| Cable Length            | 5.0m (16.40')    |
| Color - Cable Jacket    | Yellow           |
| Connector End A         | Ultra-Lock (M12) |
| Connector End B         | Pigtail          |
| Coupling Style          | Push to Lock     |
| Gender                  | Male-Pigtail     |
| Keyway                  | Single           |
| LED Indicator           | No               |
| Material - Cable Jacket | PVC              |

| Material - Connector Body     | PUR                 |
|-------------------------------|---------------------|
| Material - Contact            | Copper Alloy        |
| Material - Coupling Nut       | Nickel-plated Brass |
| Material - O-Ring             | Fluoro-elastomer    |
| Material - Plating Mating     | Gold                |
| Net Weight                    | 578.000/g           |
| Orientation                   | 90° to Pigtail      |
| Poles                         | 5                   |
| Temperature Range - Operating | -25° to +90°C       |
| Wire/Cable Type               | UL 2661             |
| Wire Size (AWG)               | 22                  |

This document was generated on Apr 12, 2024