

Part Number: 1200655109 Product Description: Micro-Change (M12) Single-Ended Cordset, 12 Poles, Male (90°) to

Pigtail, 26 AWG, PUR Cable, 2.0m (6.56')

Length

Series Number: 120065 Status: Active

Product Category: Circular Industrial Engineering Number: 80C007H45M020

Cordsets

Documents & Resources

Drawings

Drawing 1200655109_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | <u> </u> |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Circular Industrial Cordsets |
| Series | 120065 |
| Description | Micro-Change (M12) Single-Ended Cordset, 12 Poles, Male (90°) to Pigtail, 26 AWG, PUR Cable, 2.0m (6.56') Length |
| IP Rating | IP67 |
| Product Family | Brad Micro-Change (M12) Connectors |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Region | Europe |
| Туре | Single Ended |
| UPC | 884982224292 |

Agency

| CSA | LR6837 |
|-----|--------|
| | |

Electrical

| Current - Maximum per Contact | 1.5A |
|-------------------------------|-----------|
| Voltage - Maximum | 30V AC/DC |

Physical

| Cable Diameter | 6.00mm (.236") |
|---------------------------|--------------------|
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Male-Pigtail |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | PUR |
| Material - Connector Body | PUR |
| | |

| Material - Contact | Copper Alloy |
|-------------------------------|---------------------|
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 102.499/g |
| Orientation | 90° to Pigtail |
| Poles | 12 |
| Temperature Range - Operating | -25° to +80°C |
| Wire/Cable Type | UL 20549 |
| Wire Size (AWG) | 26 |

This document was generated on Jul 18, 2024