



DESOLDERING PUMP


This desoldering pump made with best material, strong spring, hi-power suction, designed for one-hand operation and is durable and ideal for circuit boards and other solder clearing work.

SUPERIOR QUALITY

- 1. Large capacity, powerful spring, simple operation, powe ful solder sucker.
- 2. One touched cylinder and holder, which are
- 3. The protector can make you safe to operate
- 4. Cleaned shaft can help the nozzle to remove the solder.
- 5. Protector styled load mechanism is conv enience to take along.

OPERATION PROCEDURE

- 1. Push the set knob for loading the cleaned shaft until the knob stops.
- 2. Melt the solder where it is intended to remove.
- 3. Aim the nozzle to the melted solder and then push the release button. Thus the solder can be sucked.
- 4. Press the release button while pushing the setknob without reloading the cylinder
- 5. Push the set-knob and then pull the protector, the load mechanism is released.




CAUTION

- 1. Don't take down the nozzle mechanically.
- 2. Don't let the solderfall into the nozzle adv oiding short - circuit.
- 3. Don't use the damaged nozzle.

MAINTENANCE

- 1. Push the set knob until it stops and then take down the nozzle.
- 2.Stuff the nozzle tinht into the cylinder holder, then press it gegtely toward the holder.
- 3. Grasp the cylinder and shaft holder and turn it anti - clock wise, pull and remove it.
- 4.Clean the piston and the inner cylinder with a brush and then oil them.
- 5.Be careful to examine and replace the nozzle if neccessary because the nozzle might be damaged if the solder is too hot.



REPL ACEMENT PARTS

NAME	TEFLON NOZZLE	PISTON RING
STYLE	GS-100N	GS-100P
MESURE MENT	© 132 ↑ 165	↑

深圳市白光电子科技有限公司 SHENZHEN BAKON ELECTRONIC TECHNOLOGY CO., LTD.

全国统一服务热线: 0755-89575688

全国统一服务热线: 0/55-895 /3688 网址(SITE): www.bakon.com 总部地址(ADD): 深圳市光明新区马田街道瑞辉大厦4楼 制造工厂(MFR): 河南白光工具有限公司 生产地址(ADD): 河南省郑州市航空港区锦荣信息科技园7栋