

# DS90UH981-Q1 4K DSI to FPD-Link IV Bridge Serializer With HDCP

## 1 Features

- Single or dual port MIPI DSI receiver
  - Compliant to D-PHY v1.2 and DSI v1.3.1
  - Packed 16/18/24/30-bit RGB and 16-bit YCbCr
  - Loosely packed 18-bit RGB and 20-bit 4:2:2
  - 1 clock lane and 1-4 configurable data lanes per D-PHY Port
  - Up to 2.5 Gbps/lane with skew calibration
  - Supports data lane swap and polarity inversion
  - Supports both burst and non-burst mode
  - SuperFrame Unpacking Capability
  - Suitable for 4K at 60Hz video resolution
- FPD-Link IV interface
  - Supports 10.8/6.75/3.375Gbps per channel; Up to 21.6Gbps over dual channels
  - Coax/STP interconnect support
  - Port Splitting to enable Y-cable interfaces
- Ultra-low latency control channel
  - Two I2C up to 1MHz (up to 3.4MHz for local bus access)
  - High speed GPIOs
- Backwards compatible
  - Integrated HDCP v1.4 with on-chip keys
  - 720P 92x and 1080P/2K 94x product families
  - ADAS 936, 954, 960, 962, 9702, 9722 deserializers
- Security and diagnostics
  - Voltage and temperature monitoring
  - Line Fault Detection
  - BIST and pattern generation
  - CRC and error diagnostics
  - Unique ID for counterfeit protection
  - ECC on control bits
- Advanced link robustness and EMC control
  - Data scrambling
  - Spread spectrum clocking generation (SSCG)
- Low power operation
  - 1.8V and 1.1V dual power supply
- AEC-Q100 qualified for automotive applications
  - AEC-Q100 grade-level 2: -40°C to +105°C
  - 64 pin QFN Wettable flanks 9mm x 9mm
  - ISO 10605 and IEC 61000-4-2 ESD compliant

## 2 Applications

- Automotive displays:
  - [Central Information Displays \(CID\)](#)
  - [Rear Seat Entertainment \(RSE\)](#)
  - [Digital instrument clusters](#)
  - [Head units and HMI modules](#)
  - [Head Up Display \(HUD\)](#)
  - [Rear view and side mirror displays](#)


## 3 Description

DS90UH981-Q1 is a MIPI DSI to FPD-Link III/IV bridge device. In conjunction with an FPD-Link IV deserializer, the chipset provides a high-speed serialized interface over low-cost 50Ω coax or STP cables. The DS90UH981-Q1 is a D-PHY v1.2 compliant device that serializes a MIPI DSI input supporting video resolutions including 4K with 30-bit color depth. The FPD-Link IV interface supports video and audio data transmission and full duplex control, including I2C and GPIO data over a single channel or dual channels. Consolidation of video data and control over two FPD-Link IV lanes reduces the interconnect size and weight and simplifies system design. EMI is minimized by the use of low voltage differential signaling, data scrambling, SSCG, and randomization. In backward compatible mode, the devices supports up to 720p and 1080p resolutions with 24-bit color depth over a single/dual link as well as HDCP v1.4 support when paired with an HDCP-capable deserializer. In ADAS compatible mode, the device is interoperable with 936, 95x, 96x & 97x deserializers supporting resolutions up to 8MP+/40fps.

### Package Information

| PART NUMBER  | PACKAGE <sup>(1)</sup> | PACKAGE SIZE <sup>(2)</sup> |
|--------------|------------------------|-----------------------------|
| DS90UH981-Q1 | RTD (VQFNFP, 64)       | 9.00mm × 9.00mm             |

- (1) For all available packages, see [Section 6](#).
- (2) The package size (length × width) is a nominal value and includes pins, where applicable.



Simplified Application Diagram



**Table of Contents**

|                                                 |          |                                                                |          |
|-------------------------------------------------|----------|----------------------------------------------------------------|----------|
| <b>1 Features</b> .....                         | <b>1</b> | 4.2 Trademarks.....                                            | <b>3</b> |
| <b>2 Applications</b> .....                     | <b>1</b> | 4.3 Electrostatic Discharge Caution.....                       | <b>3</b> |
| <b>3 Description</b> .....                      | <b>1</b> | 4.4 Glossary.....                                              | <b>3</b> |
| <b>4 Device and Documentation Support</b> ..... | <b>3</b> | <b>5 Revision History</b> .....                                | <b>3</b> |
| 4.1 Documentation Support.....                  | <b>3</b> | <b>6 Mechanical, Packaging, and Orderable Information</b> .... | <b>4</b> |

## 4 Device and Documentation Support

### 4.1 Documentation Support

#### 4.1.1 Related Documentation

For related documentation see the following:

- Texas Instruments, [Soldering Specifications](#) application note
- Texas Instruments, [Semiconductor and IC Package Thermal Metrics](#) application note
- Texas Instruments, [Leadless Leadframe Package \(LLP\)](#) application note
- Texas Instruments, [LVDS Owner's Manual](#)
- Texas Instruments, [I2C Communication Over FPD-Link III with Bidirectional Control Channel](#) application note
- Texas Instruments, [Exploring the Internal Test Pattern Generation Feature of 720p FPD-Link III Devices](#) application note
- Texas Instruments, [I2C Bus Pullup Resistor Calculation](#) application note
- Texas Instruments FPD-Link Learning Center, [FPD-Link Fundamental Material](#) video series
- Texas Instruments, [Ten tips for successfully designing with automotive EMC/EMI requirements](#)
- Texas Instruments, [Serial Line-Fault Detection](#) (Contact TI)

### 4.2 Trademarks

All trademarks are the property of their respective owners.

### 4.3 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

### 4.4 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

## 5 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| DATE          | REVISION | NOTES           |
|---------------|----------|-----------------|
| February 2024 | *        | Initial Release |

## 6 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| DS90UH981RTDRQ1  | ACTIVE        | VQFN         | RTD                | 64   | 2000           | RoHS & Green    | NIPDAUAG                             | Level-3-260C-168 HR  | -40 to 105   | UH981                   | <a href="#">Samples</a> |
| DS90UH981RTDTQ1  | ACTIVE        | VQFN         | RTD                | 64   | 250            | RoHS & Green    | NIPDAUAG                             | Level-3-260C-168 HR  | -40 to 105   | UH981                   | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.




## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device          | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-----------------|--------------|-----------------|------|-----|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| DS90UH981RTDTQ1 | VQFN         | RTD             | 64   | 250 | 180.0              | 16.4               | 9.3     | 9.3     | 1.1     | 12.0    | 16.0   | Q2            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal


| Device          | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|-----------------|--------------|-----------------|------|-----|-------------|------------|-------------|
| DS90UH981RTDTQ1 | VQFN         | RTD             | 64   | 250 | 210.0       | 185.0      | 35.0        |

## GENERIC PACKAGE VIEW

**RTD 64**

**VQFNP - 0.9 mm max height**

PLASTIC QUAD FLATPACK - NO LEAD



Images above are just a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.

4205146/D

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2024, Texas Instruments Incorporated