

## Features

- Low operating voltage:  $\pm 24V$
- Ultra low capacitance: 0.3pF typical
- Ultra low leakage: nA level
- Low operating voltage:
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
- – IEC 61000-4-2 (ESD) immunity test
  - Air discharge:  $\pm 20kV$
  - Contact discharge:  $\pm 15kV$
- – IEC61000-4-5 (Lightning) 2A (8/20 $\mu s$ )
- RoHS Compliant
- Lead Finish: NiPdAu



## Mechanical Characteristics

- Package: DFN1006-2(0402)
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below
- Shipping Qty :15000pcs Or 10000/7Inch Tape & Reel

## Applications

- VGA,DVI,SDI,USB1.0,USB2.0,USB3.0,USB3.1
- High Definition Multi-Media Interface(HDMI1.3/1.4/2.0
- Serial and Parallel Ports
- Notebooks, Desktops, Servers
- Peripherals

## Dimensions and Pin Configuration



**Absolute Maximum Ratings** (Tamb=25°C unless otherwise specified)

| Parameter                       | Symbol | Value       | Unit |
|---------------------------------|--------|-------------|------|
| Peak Pulse Power (8/20μs)       | Ppk    | 90          | W    |
| Peak Pulse Current (8/20μs)     | Ipp    | 2           | A    |
| ESD per IEC 61000-4-2 (Air)     | VESD   | ±20         | kV   |
| ESD per IEC 61000-4-2 (Contact) |        | ±15         |      |
| Operating Temperature Range     | TJ     | -55 to +125 | °C   |
| Storage Temperature Range       | Tstg   | -55 to +150 | °C   |

**Electrical Characteristics** (TA=25°C unless otherwise specified)

| Parameter               | Symbol | Min  | Typ | Max | Unit | Test Condition        |
|-------------------------|--------|------|-----|-----|------|-----------------------|
| Reverse Working Voltage | VRWM   |      |     | 24  | V    |                       |
| Breakdown Voltage       | VBR    | 26.4 |     |     | V    | IT = 1mA              |
| Reverse Leakage Current | IR     |      |     | 0.1 | uA   | VRWM = 24V            |
| Clamping Voltage        | VC     |      |     | 40  | V    | Ipp=1A(8x 20us pulse) |
| Clamping Voltage        | VC     |      |     | 55  | V    | Ipp=2A(8x 20us pulse) |
| Junction Capacitance    | CJ     |      | 0.3 |     | pF   | VR = 0V, f = 1MHz     |

### Typical Performance Characteristics ( $T_A=25^{\circ}\text{C}$ unless otherwise Specified)

Fig1. 8/20 $\mu\text{s}$  Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




## DFN1006-2 Package Outline Drawing (0402)



| SYM | DIMENSIONS  |      |      |           |       |       |
|-----|-------------|------|------|-----------|-------|-------|
|     | MILLIMETERS |      |      | INCHES    |       |       |
|     | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A   | 0.45        | 0.50 | 0.55 | 0.018     | 0.020 | 0.022 |
| A1  | 0.00        | 0.02 | 0.05 | 0.000     | 0.001 | 0.002 |
| b   | 0.45        | 0.50 | 0.55 | 0.018     | 0.020 | 0.022 |
| c   | 0.12        | 0.15 | 0.18 | 0.005     | 0.006 | 0.007 |
| D   | 0.95        | 1.00 | 1.05 | 0.037     | 0.039 | 0.041 |
| e   | 0.65 BSC    |      |      | 0.026 BSC |       |       |
| E   | 0.55        | 0.60 | 0.65 | 0.022     | 0.024 | 0.026 |
| L   | 0.20        | 0.25 | 0.30 | 0.008     | 0.010 | 0.012 |
| h   | 0.07        | 0.12 | 0.17 | 0.003     | 0.005 | 0.007 |

## Suggested Land Pattern



| SYM | DIMENSIONS  |        |
|-----|-------------|--------|
|     | MILLIMETERS | INCHES |
| X   | 0.60        | 0.024  |
| Y1  | 0.50        | 0.020  |
| Y2  | 0.30        | 0.012  |
| Y3  | 0.80        | 0.032  |
| Z   | 1.30        | 0.052  |