

### SPECIFICATIONS

Current Rating: 3Amps  
 Insulation Resistance: 1000MΩ Min  
 Contact Resistance: 20mΩ Max  
 Withstanding Voltage: AC 1000V  
 Operation Temperature: -40° to+105°  
 Contact Material: Brass  
 Standard: PA6T  
 Insulator Material: Polyester (UL 94V-0)  
 Contact Plating: Gold Flash  
 Max. Processing Temp: 200° C for 30-60seconds  
 (220° C for 5seconds)

**RECOMMEND P. C. B LAYOUT**  
PCB TOLERANCE: ±0.05 (TOP VIEW)

<span style="font-size: 24px; font-weight: bold; vertical-align: middle;">深圳市韩下电子有限公司</span>										No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B																								
<p>UNLESS OTHERWISE SPECIFIED TOLERANCE</p> <table style="font-size: 10px;"> <tr> <td>X</td><td>: ±0.30</td> <td>X°</td><td>: ±5°</td> </tr> <tr> <td>X.X</td><td>: ±0.25</td> <td>X.X°</td><td>: ±1°</td> </tr> <tr> <td>X.XX</td><td>: ±0.20</td> <td>X.XX°</td><td>: ±0.5°</td> </tr> </table> <p>DRAWN NAME: HX PM2.54-1x4P ZC H11</p> <table style="font-size: 8px;"> <tr> <td>SIZE</td><td>A4</td> <td>SCALE</td><td>N:1</td> <td>PROUCT NO.</td><td></td> </tr> <tr> <td>REV</td><td>A</td> <td>UNIT</td><td>mm</td> <td>PROJECT</td><td></td> </tr> </table> <p>DRAW: 黄彬 2022/07/18    CHECKED: 张伟 2022/07/18    APPROVED: 罗小春 2022/07/18</p>										X	: ±0.30	X°	: ±5°	X.X	: ±0.25	X.X°	: ±1°	X.XX	: ±0.20	X.XX°	: ±0.5°	SIZE	A4	SCALE	N:1	PROUCT NO.		REV	A	UNIT	mm	PROJECT		1	0.00	2.54	11	25.40	27.94	21	50.80	53.34	31	76.20	78.74
										X	: ±0.30	X°	: ±5°																																
										X.X	: ±0.25	X.X°	: ±1°																																
										X.XX	: ±0.20	X.XX°	: ±0.5°																																
										SIZE	A4	SCALE	N:1	PROUCT NO.																															
										REV	A	UNIT	mm	PROJECT																															
										2	2.54	5.08	12	27.94	30.48	22	53.34	55.88	32	78.74	81.28																								
										3	5.08	7.62	13	30.48	33.02	23	55.88	58.42	33	81.28	83.82																								
										4	7.62	10.16	14	33.02	35.56	24	58.42	60.96	34	83.82	86.36																								
										5	10.16	12.70	15	35.56	38.10	25	60.96	63.50	35	86.36	88.90																								
6	12.70	15.24	16	38.10	40.64	26	63.50	66.04	36	88.90	91.44																																		
7	15.24	17.78	17	40.64	43.18	27	66.04	68.58	37	91.44	93.98																																		
8	17.78	20.32	18	43.18	45.72	28	68.58	71.12	38	93.98	96.52																																		
9	20.32	22.86	19	45.72	48.26	29	71.12	73.66	39	96.52	99.06																																		
10	22.86	25.40	20	48.26	50.80	30	73.66	76.20	40	99.06	101.60																																		