

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Distribution block, bridged internally, nom. voltage: 500 V, nominal current: 17.5 A, connection method: Push-in connection, number of connections: 6, cross section: 0.14 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 26 - 14, width: 12.5 mm, color: yellow, mounting type: NS 15

### Your advantages

- ✓ Space-saving, thanks to the compact design
- ✓ Flexible use, thanks to DIN rail and direct mounting
- ✓ Space-saving potential distribution, thanks to compact micro potential distributors
- ✓ Convenient test options, thanks to test openings at every terminal point
- ✓ Clear arrangement thanks to marking of all terminal points



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 20 pc                                                                                                   |
| Minimum order quantity               | 20 pc                                                                                                   |
| GTIN                                 | <br>4 055626 433646 |
| GTIN                                 | 4055626433646                                                                                           |
| Weight per Piece (excluding packing) | 5.880 g                                                                                                 |
| Custom tariff number                 | 85369010                                                                                                |
| Country of origin                    | Poland                                                                                                  |

### Technical data

#### General

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Note                  | Notes on operation The blocks can be bridged with one another via the conductor shaft. For corresponding plug-in bridges, see accessories |
|                       | Notes on operation The D-PTFIX 1,5 cover (accessory) must be placed on the end of the terminal strip                                      |
| Number of levels      | 1                                                                                                                                         |
| Number of connections | 6                                                                                                                                         |
| Potentials            | 1                                                                                                                                         |
| Nominal cross section | 1.5 mm <sup>2</sup>                                                                                                                       |

# Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

## Technical data

### General

|                                                                                           |                                     |
|-------------------------------------------------------------------------------------------|-------------------------------------|
| Color                                                                                     | yellow                              |
| Insulating material                                                                       | PA                                  |
| Flammability rating according to UL 94                                                    | V0                                  |
| Rated surge voltage                                                                       | 6 kV                                |
| Degree of pollution                                                                       | 3                                   |
| Overvoltage category                                                                      | III                                 |
| Insulating material group                                                                 | I                                   |
| Maximum power dissipation for nominal condition                                           | 0.56 W                              |
| Ambient temperature (operation)                                                           | -60 °C ... 130 °C                   |
| Maximum load current                                                                      | 26 A                                |
| Maximum total current                                                                     | 26 A                                |
| Nominal current $I_N$                                                                     | 17.5 A                              |
| Nominal voltage $U_N$                                                                     | 500 V                               |
| Open side panel                                                                           | No                                  |
| Shock protection test specification                                                       | DIN EN 50274 (VDE 0660-514):2002-11 |
| Back of the hand protection                                                               | guaranteed                          |
| Finger protection                                                                         | guaranteed                          |
| Result of surge voltage test                                                              | Test passed                         |
| Surge voltage test setpoint                                                               | 7.3 kV                              |
| Result of power-frequency withstand voltage test                                          | Test passed                         |
| Power frequency withstand voltage setpoint                                                | 1.89 kV                             |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed                         |
| Result of bending test                                                                    | Test passed                         |
| Bending test rotation speed                                                               | 10 rpm                              |
| Bending test turns                                                                        | 135                                 |
| Bending test conductor cross section/weight                                               | 0.14 mm <sup>2</sup> / 0.2 kg       |
|                                                                                           | 1.5 mm <sup>2</sup> / 0.4 kg        |
| Tensile test result                                                                       | Test passed                         |
| Conductor cross section tensile test                                                      | 0.14 mm <sup>2</sup>                |
| Tractive force setpoint                                                                   | 10 N                                |
| Conductor cross section tensile test                                                      | 1.5 mm <sup>2</sup>                 |
| Tractive force setpoint                                                                   | 40 N                                |
| Result of tight fit on support                                                            | Test passed                         |
| Tight fit on carrier                                                                      | NS 15                               |
| Setpoint                                                                                  | 5 N                                 |
| Result of voltage-drop test                                                               | Test passed                         |
| Requirements, voltage drop                                                                | ≤ 3.2 mV                            |
| Result of temperature-rise test                                                           | Test passed                         |
| Short circuit stability result                                                            | Test passed                         |
| Conductor cross section short circuit testing                                             | 1.5 mm <sup>2</sup>                 |

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Technical data

#### General

|                                                                     |                                                |
|---------------------------------------------------------------------|------------------------------------------------|
| Short-time current                                                  | 0.18 kA                                        |
| Result of thermal test                                              | Test passed                                    |
| Ageing test for screwless modular terminal block temperature cycles | 192                                            |
| Proof of thermal characteristics (needle flame) effective duration  | 30 s                                           |
| Result of aging test                                                | Test passed                                    |
| Oscillation, broadband noise test result                            | Test passed                                    |
| Test specification, oscillation, broadband noise                    | DIN EN 50155 (VDE 0115-200):2008-03            |
| Test spectrum                                                       | Service life test category 2, bogie-mounted    |
| Test frequency                                                      | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level                                                           | $6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$      |
| Acceleration                                                        | 3.12 g                                         |
| Test duration per axis                                              | 5 h                                            |
| Test directions                                                     | X-, Y- and Z-axis                              |
| Shock test result                                                   | Test passed                                    |
| Test specification, shock test                                      | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                                          | Half-sine                                      |
| Acceleration                                                        | 30g                                            |
| Shock duration                                                      | 18 ms                                          |
| Number of shocks per direction                                      | 3                                              |
| Test directions                                                     | X-, Y- and Z-axis (pos. and neg.)              |
| Behavior in fire for rail vehicles (DIN 5510-2)                     | Test passed                                    |
| Flame test method (DIN EN 60695-11-10)                              | V0                                             |
| Oxygen index (DIN EN ISO 4589-2)                                    | >32 %                                          |
| NF F16-101, NF F10-102 Class I                                      | 2                                              |
| NF F16-101, NF F10-102 Class F                                      | 2                                              |
| Surface flammability NFPA 130 (ASTM E 162)                          | passed                                         |
| Specific optical density of smoke NFPA 130 (ASTM E 662)             | passed                                         |
| Smoke gas toxicity NFPA 130 (SMP 800C)                              | passed                                         |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                    | 28 MJ/kg                                       |
| Fire protection for rail vehicles (DIN EN 45545-2) R22              | HL 1 - HL 3                                    |
| Fire protection for rail vehicles (DIN EN 45545-2) R23              | HL 1 - HL 3                                    |
| Fire protection for rail vehicles (DIN EN 45545-2) R24              | HL 1 - HL 3                                    |
| Fire protection for rail vehicles (DIN EN 45545-2) R26              | HL 1 - HL 3                                    |

#### Dimensions

|              |         |
|--------------|---------|
| Width        | 12.5 mm |
| Length       | 21.6 mm |
| Height NS 15 | 27.4 mm |

#### Connection data

|                   |                    |
|-------------------|--------------------|
| Connection method | Push-in connection |
|-------------------|--------------------|

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Technical data

#### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Connection in acc. with standard                                           | IEC 60947-7-1        |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 2.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                           | 26                   |
| Conductor cross section AWG max.                                           | 14                   |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible                                 | 24                   |
| Max. AWG conductor cross section, flexible                                 | 12                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 1.5 mm <sup>2</sup>  |
| Stripping length                                                           | 8 mm ... 10 mm       |
| Internal cylindrical gage                                                  | A1 / B1              |

#### Standards and Regulations

|                                                        |               |
|--------------------------------------------------------|---------------|
| Connection in acc. with standard                       | IEC 60947-7-1 |
| Flammability rating according to UL 94                 | V0            |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3   |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3   |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3   |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3   |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

#### Circuit diagram



### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141100 |

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141120 |
| eCl@ss 9.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |
| ETIM 6.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

#### Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

#### Approval details

|                    |                                                                                     |                                                                                                                                         |       |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                    | D                                                                                   | B                                                                                                                                       | C     |
| Nominal voltage UN | 300 V                                                                               | 300 V                                                                                                                                   | 150 V |
| Nominal current IN | 10 A                                                                                | 15 A                                                                                                                                    | 15 A  |
| mm²/AWG/kcmil      | 26-14                                                                               | 26-14                                                                                                                                   | 26-14 |

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Approvals

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| UL Recognized      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | D                                                                                 | B                                                                                                                                                     | C            |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 | 150 V        |
| Nominal current IN | 10 A                                                                              | 15 A                                                                                                                                                  | 15 A         |
| mm²/AWG/kcmil      | 26-14                                                                             | 26-14                                                                                                                                                 | 26-14        |

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| cUL Recognized     |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | D                                                                                 | B                                                                                                                                                     | C            |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 | 150 V        |
| Nominal current IN | 10 A                                                                              | 15 A                                                                                                                                                  | 15 A         |
| mm²/AWG/kcmil      | 26-14                                                                             | 26-14                                                                                                                                                 | 26-14        |

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.AI30.B.01102 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| cULus Recognized |  |
|------------------|-------------------------------------------------------------------------------------|

### Accessories

#### Accessories

##### DIN rail

DIN rail, unperforated - NS 15 UNPERF 2000MM - 1401695



DIN rail, unperforated, Standard profile, width: 15 mm, height: 5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail perforated - NS 15 PERF 2000MM - 1401682



DIN rail perforated, Standard profile, width: 15 mm, height: 5.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Accessories

---

#### DIN rail perforated - NS 15 AL PERF 2000MM - 1401763



DIN rail perforated, Standard profile, width: 15 mm, height: 5.5 mm, acc. to EN 60715, material: Aluminum, uncoated, length: 2000 mm, color: silver

---

#### DIN rail perforated - NS 15 WH PERF 2000MM - 1204096



DIN rail perforated, Standard profile, width: 15 mm, height: 5.5 mm, acc. to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

---

#### End block

##### End clamp - CLIPFIX 15 - 3022263



Snap-on end bracket, to be snapped onto NS 15 DIN rail

---

#### End cover

##### End cover - D-PTFIX 1,5 - 3003254



End cover, for use in DIN rail mounting, length: 19.9 mm, width: 2.2 mm, height: 17.7 mm, color: gray

---

#### Insulating sleeve

##### Insulating sleeve - ISH 1,5/0,2 - 3206131



Insulating sleeve, color: white

---

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Accessories

Insulating sleeve - ISH 1,5/0,5 - 3031034



Insulating sleeve, color: gray

---

### Jumper

Plug-in bridge - FBS 2-4 - 3030116



Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: red

---

Plug-in bridge - FBS 2-4 BU - 3030117



Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: blue

---

Plug-in bridge - FBS 2-4 GY - 3030118



Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: gray

---

### Labeled terminal marker

Marking foil for zack marker strip - SK 3,8 REEL P4,15 WH CUS - 0825990



Marking foil for zack marker strip, white, labeled according to customer specifications, mounting type: adhesive, for terminal block width: 4.15 mm, lettering field size: continuous x 3.8 mm

---

### Screwdriver tools

## Distribution block - PTFIX 6X1,5-NS15A YE - 3002955

### Accessories

Screwdriver - SZF 0-0,4X2,5 - 1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

---

### Terminal marking

Marking foil for zack marker strip - TML (EX3,8)R - 0801837



Marking foil for zack marker strip, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, for terminal block width: 30000 mm, lettering field size: 30,000 x 3.8 mm

---

Marking foil for zack marker strip - TML (104X3,8)R - 0801833



Marking foil for zack marker strip, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, for terminal block width: 104 mm, lettering field size: 104 x 3.8 mm

---

### Test plug terminal block

Accessories - MPS-MT 1-S4-B RD - 1982800



Accessories

---

Test plugs - MPS-MT 1-S - 1944372



Test plug, consisting of 1.0 mm Ø test pin and 2.0 mm Ø socket