

1002635

https://www.phoenixcontact.com/us/products/1002635

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 405 mm



Your advantages

- · Protection against polarity reversal phase rotation not possible
- · Quick, complete out-of-the-box system
- Compact design compared to conventional power distribution

Commercial data

Item number	1002635
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C470
Product key	CK7811
Catalog page	Page 52 (C-5-2019)
GTIN	4055626468204
Weight per piece (including packing)	1,410.3 g
Weight per piece (excluding packing)	1,367.3 g
Customs tariff number	85369095
Country of origin	DE



1002635

https://www.phoenixcontact.com/us/products/1002635

Technical data

Notes

Assembly note	We recommend using the high DIN rail (35x15) for optimum
	stability and maximum load. For detailed technical information,
	please refer to the packing slip. Torque for screwing on the
	power distribution board: 1.5 Nm (13lb-in).

Product properties

Product type	Assembly adapter
Product family	CrossPowerSystem
Data management status	
Article revision	00

Electrical properties

Rated voltage	600 V DC (IEC)
	690 V AC (IEC)
	600 V AC/DC (UL)
Rated peak withstand current	25 kA
Rated current	125 A (IEC)
	100 A (UL)
Rated insulation voltage	800 V AC
Rated surge voltage	6 kV

Dimensions

Width	405 mm
Height	160 mm
Depth	45.1 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection IP20	
---------------------------	--

Approvals

UL data

SCCR	10 kA (unprotected)
	100 kA (protected)
	100 kA (CB 125 A/480 V AC)
	65 kA (CB 125 A/600 V AC)
	100 A (Class J 175 A)

Standards and regulations

Standards/regulations IEC 6143	39-2
--------------------------------	------



1002635

https://www.phoenixcontact.com/us/products/1002635

GB/T 7251.1



1002635

https://www.phoenixcontact.com/us/products/1002635

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1002635



EAC

Approval ID: RU C-DE.A*30.B.01742



EAC

Approval ID: RU*DE*08.B.01841/19



UL Listed

Approval ID: E123528



cUL Listed

Approval ID: E123528

cULus Listed



1002635

https://www.phoenixcontact.com/us/products/1002635

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27371392
ECLASS-13.0	27371392
ECLASS-12.0	27371392
ETIM	
ETIM 9.0	EC002498
UNSPSC	

39121100



1002635

https://www.phoenixcontact.com/us/products/1002635

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com