

AX103917 Faceplates and Panels - FiberExpress Ultra Cassette Rear assembly



For more Information
please call

1-800-Belden1



General Description:

FiberExpress Ultra Cassette Rear assembly, Black.

Usage (Overall)

| | |
|-------------------------------|---|
| Suitable Applications: | FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room, Data Centers |
| Related Parts: | FiberExpress Ultra Frames, Bezels, Trays |

Physical Characteristics (Connectivity)

Capacity

| | |
|-----------------------|--|
| Max. Capacity: | 12 Fibers (SC, SCD, ST, FC); 24 Fibers (LCD, MT-RJ). 1 Frames (6 Bezels) |
|-----------------------|--|

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 1.450 | 4.110 | 6.130 |

Materials

Materials:

| Description | Material |
|-------------|-------------------|
| Cassette | Plastic - UL94V-0 |

Color

| | |
|---------------|-------|
| Color: | Black |
|---------------|-------|

Weight

| | |
|----------------|------------|
| Weight: | 0.100 lbs. |
|----------------|------------|

Packaging

| | |
|-------------------|--|
| Packaging: | Individually packaged in a suitable plastic bag. |
|-------------------|--|

Mechanical Characteristics (Connectivity)

| | |
|-------------------------------------|----------------|
| Storage Temperature Range: | -40°C To +70°C |
| Operating Temperature Range: | -10°C To +60°C |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|--|------------|
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 05/20/2008 |
| MIL Order #39 (China RoHS): | Yes |

Suitability

| | |
|------------------------------|-----|
| Suitability - Indoor: | Yes |
|------------------------------|-----|

Notes (Overall)

Notes: For more information, please refer to the following New Product Bulletin: NP287 Frames and Bezels

Product Family

Part Numbers:

| Description | Multimode OM1 - 62.5um | Multimode OM2 - 50um | Multimode OM3 - 50um | Single-Mode Enhance OS2 | Others |
|-------------------------------------|------------------------|----------------------|----------------------|-------------------------|--------|
| ST-MPO 6 fibers | AX103619 | AX103673 | AX103691 | AX103799 | - |
| ST-MPO 12 fibers | AX103638 | AX103680 | AX103710 | AX103818 | - |
| SC Duplex-MPO - 6 fibers | AX103620 | AX103674 | AX103692 | AX103800 | - |
| SC Duplex w/shutter-MPO - 6 fibers | AX103621 | AX103675 | AX103693 | AX103801 | - |
| SC Duplex-MPO - 12 fibers | AX103639 | AX103681 | AX103711 | AX103819 | - |
| LC Duplex-MPO - 6 fibers | AX103622 | AX103676 | AX103694 | AX103802 | - |
| LC Duplex w/shutter-MPO - 6 fibers | AX103623 | AX103677 | AX103695 | AX103803 | - |
| LC Duplex-MPO - 12 fibers | AX103641 | AX103683 | AX103713 | AX103821 | - |
| LC Duplex w/shutter-MPO - 12 fibers | AX103642 | AX103684 | AX103714 | AX103822 | - |

AX103917 Faceplates and Panels - FiberExpress Ultra Cassette Rear assembly

| | | | | | |
|--|----------|----------|----------|----------|----------|
| LC Duplex-MPO - 24 fibers | AX103657 | AX103687 | AX103729 | AX103837 | - |
| MT-RJ(M)-MPO - 6 fibers | AX103625 | AX103679 | AX103697 | AX103805 | - |
| MT-RJ(M)-MPO - 12 fibers | AX103644 | AX103686 | AX103716 | AX103824 | - |
| MT-RJ(M)-MPO - 24 fibers | AX103660 | AX103690 | AX103732 | AX103840 | - |
| Cassette Rear assembly | - | - | - | - | AX103917 |
| Universal Frame w/Cassette Rear assembly | - | - | - | - | AX103918 |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|--------|-------|-------------|-------|-------|-----------|
|--------|-------|-------------|-------|-------|-----------|

Revision Number: 0 Revision Date: 09-08-2009

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.