

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648
<https://www.phoenixcontact.com/us/products/1542648>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 4-position, Socket, straight, M12-SPEEDCON, coding: D, Rear mounting, M12 x 1, THR solder connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239956

Commercial data

Item number	1542648
Packing unit	60 pc
Minimum order quantity	60 pc
Sales key	AB23
Product key	ABQAIA
Catalog page	Page 90 (C-2-2013)
GTIN	4046356097918
Weight per piece (including packing)	11.225 g
Weight per piece (excluding packing)	11.225 g
Customs tariff number	85366990
Country of origin	DE

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648

<https://www.phoenixcontact.com/us/products/1542648>

Technical data

Notes

General	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling)
Order information:	Lock nut is included in the scope of delivery

Mounting

Mounting type	Rear mounting M12 x 1 With flat nut
Assembly note	With flat nut

Product properties

Product type	Circular connectors (device side)
Application	Data
	Signal
Number of positions	4
Shielded	no
Coding	D
Thread type	M12

Data management status

Article revision	12
------------------	----

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	HB
Seal material	FKM / EPDM
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PPA
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	250 V
Nominal current I_N	4 A

Connection data

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648
<https://www.phoenixcontact.com/us/products/1542648>

Conductor connection	
Connection method	THR solder connection
Contact connection type	Socket

Connector

Connection 1	
Head design	Socket
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	D

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
	IP67
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)


SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting

1542648

<https://www.phoenixcontact.com/us/products/1542648>

Drawings

Schematic diagram



Pin assignment M12 socket, 4-pos., D-coded, female side

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648
<https://www.phoenixcontact.com/us/products/1542648>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1542648>

	UL Recognized Approval ID: E118976-20100522			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	250 V	4 A	22 - 22	-

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648
<https://www.phoenixcontact.com/us/products/1542648>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSIV-FSD-4CON-L180 SCOTHR - Device connector rear mounting



1542648
<https://www.phoenixcontact.com/us/products/1542648>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	68837f82-aea4-4aac-a2d7-bb93d9cd9859

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com