


STANDARD & RUGGED USB 2.0

USB-B/USBR-B SERIES



SPECIFICATIONS

Insulator Material:

High Temperature

Thermoplastic Contact Material:

Phosphor Bronze

Plating: Gold on Contacts, Nickel on Shell, Tin on Tails

Operating Temp Range: -50 °C to +85 °C

Voltage Rating:

30 VAC **Cycles:** 1500

(maximum number of cycles tested) **Packaging:**

Packaged and shipped in Bulk Packaging Trays; Trays suitable for automation are

available upon request. **Lead-Free Solderable:**

USB-SM=Yes USB-TH= Yes (Wave Solder only) USBR=Yes (Wave Solder only)

TID Number: USB-B-S-X-X-TH (61001155)

SERIES

USB

= Standard Connector

USBR

= Increased Retention Connector

(Complies with Class 1, DIV II minimum withdrawal

requirement of 15N)





PLATING

-F

= Gold

Flash on Mating Area, Tin on Tails

-S = 30 μ" (0.76 μm) Gold on

Mating Area, Tin on Tails

COLOR

-B = Black (USB only)

-W = White (USB only)

-0 = Orange (USBR only) _TH

TERMINATION

= Through-hole

-SM = Surface Mount (USB only)

-VT = Vertical Top Entry


OTHER OPTION


-TR


= Tape and Reel (-SM only)

= Full Reel Tape & Reel (must order maximum quantity per reel; contact Samtec for quantity breaks) (–SM åonly)

MATING / UNMATING FORCE (100 CYCLES)		
SERIES	MATING	UNMATING
USB	5.3 (23.59 N)	6.1 (27.15 N)
USBR	11.8 (52.51 N)	11.5 (51.18 N)







View complete specifications at: samtec.com?USB-B or samtec.com?USBR-B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

USB-B-S-F-B-TH
USB-B-S-F-B-SM-R
USB-B-S-S-B-VT
USB-B-S-F-W-SM-TR
USB-B-S-S-B-SM
USB-B-S-S-W-TH

USB-B-S-F-B-SM
USB-B-S-S-W-SM
USB-B-S-F-B-SM-TR
USB-B-S-S-B-SM-R
USB-B-S-F-W-SM-R
USB-B-S-F-B-VT-R
USB-B-S-F-B-VT-R
USB-B-S-F-B-VT-R
USB-B-S-F-B-VT-R
USB-B-S-S-W-SM-R
USB-B-S-S-W-SM-R
USB-B-S-S-W-SM-R
USB-B-S-S-W-SM-R
USB-B-S-S-W-SM-R-TR
USB-B-S-F-B-SM-R-TR
USB-B-S-F-W-SM-R-TR
USB-B-S-F-W-SM-R-TR
USB-B-S-F-W-SM-R-TR
USB-B-S-F-W-SM-R-TR
USB-B-S-F-W-SM-R-TR
USB-B-S-S-W-TH-R-TR
USB-B-S-S-W-TH-R-TR
USB-B-S-S-W-TH-R-TR
USB-B-S-S-W-TH-R-TR
USB-B-S-F-W-TH-R-TR
<td