


## UNIVERSAL TRANSIENT BARRIER, DUAL PAIR, 100-120 VAC, 60-154 VDC UN

### CATALOG NUMBER

**UTB110DP**



### CERTIFICATIONS



### FEATURES


- Compact design universal transient barrier provides protection of low-voltage circuits and transducers
- Separate plug and base design allows hot swappable module replacement
- Multi-stage protection and fine over-voltage protection helps ensure lowest residual surge voltages reach sensitive equipment
- Common-mode and differential-mode protection protects against both possible surge conditions
- Surge rating to 20 kA 8/20  $\mu$ s is ideal for exposed wiring
- Allows for protection of 25 analog signals or 50 digital signals per linear foot (0,3 m) of DIN rail space

### PRODUCT ATTRIBUTES

- Nominal System Voltage ( $U_n$ ): 100 - 120 VAC; 60 - 154 VDC
- Max Continuous Operating Voltage ( $U_c$ ): 150 VAC; 170 VDC
- Rated Load Current ( $I_L$ ): 800mA
- Frequency: 3 MHz
- Loop Resistance: 0.6  $\Omega$
- Max Discharge Current ( $I_{max}$ ), L+L-PE: 20kA 8/20  $\mu$ s
- Protection Modes: Common; Differential
- Technology: Gas Discharge Tube (GDT); Metal Oxide Varistor (MOV); Silicon Avalanche Diode (SAD)
- Voltage Protection Level ( $U_p$ ), L-L: 220 V @ 3 kA
- Connection, Stranded: #18 min

Mounting: 35 mm top hat DIN rail
Temperature: -4 to 149 °F
Enclosure Material: UL® 94V-0 Thermoplastic
Enclosure Rating: IP 20;NEMA®-1
Depth (D): 3.35"
Height (H): 3.54"
Width (W): 0.47"
Unit Weight: 0.2 lb
Certification Details: UL® 497B
Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C
Replacement Module: UTB110DPM

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**  
+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

**Europe**  
Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

**Europe**  
Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

**APAC**  
Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500