

SACC-DSIV-MS-4CON-L90 SCO - Device connector
rear mounting

1436589
<https://www.phoenixcontact.com/us/products/1436589>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, 4-position, Pin, angled, M12-SPEEDCON, coding: A, Rear mounting, M12 x 1, Solder pins, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1239621

Commercial data

Item number	1436589
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	AB26
Product key	ABQEGI
Catalog page	Page 30 (PC-2009)
GTIN	4046356438650
Weight per piece (including packing)	12.6 g
Weight per piece (excluding packing)	11.89 g
Customs tariff number	85366990
Country of origin	DE

SACC-DSIV-MS-4CON-L90 SCO - Device connector rear mounting



1436589

<https://www.phoenixcontact.com/us/products/1436589>

Technical data

Notes

Order information:	Lock nut is included in the scope of delivery
--------------------	---

Mounting

Mounting type	Rear mounting M12 x 1 With flat nut
Assembly note	With flat nut

Product properties

Product type	Circular connectors (device side)
Number of positions	4
Shielded	no
Coding	A
Thread type	M12

Data management status

Article revision	07
------------------	----

Insulation characteristics

Overvoltage category	II
Degree of pollution	3

Material specifications

Flammability rating according to UL 94	V0
Seal material	NBR
Contact material	CuZn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Zinc die-cast, nickel-plated

Electrical properties

Contact resistance	$\leq 3 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ M}\Omega$
Nominal voltage U_N	250 V
Nominal current I_N	4 A

Connection data

Conductor connection

Connection method	Solder pins
Contact connection type	Pin

Connector

SACC-DSIV-MS-4CON-L90 SCO - Device connector rear mounting



1436589

<https://www.phoenixcontact.com/us/products/1436589>

Connection 1

Head design	Pin
Head cable outlet	angled
Head thread type	M12
Head locking type	SPEEDCON
Coding	A

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-25 °C ... 85 °C (Plug / socket)

SACC-DSIV-MS-4CON-L90 SCO - Device connector rear mounting




1436589

<https://www.phoenixcontact.com/us/products/1436589>

Drawings

Schematic diagram



Pin assignment M12 plug, 4-pos., A-coded, view plug side

1436589
<https://www.phoenixcontact.com/us/products/1436589>

Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1436589>

	UL Recognized Approval ID: E118976-20100522			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
	250 V	4 A	22 - 22	-

SACC-DSIV-MS-4CON-L90 SCO - Device connector rear mounting



1436589

<https://www.phoenixcontact.com/us/products/1436589>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SACC-DSIV-MS-4CON-L90 SCO - Device connector rear mounting



1436589

<https://www.phoenixcontact.com/us/products/1436589>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	e24439f1-e3dc-46a5-8899-d2e40d365866

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com