

1	2	3	4	5	6	7	8																																				
<div><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div>HARTING</div><div>ix</div></div><div><div>Industrial®</div><div>type B</div></div></div></div><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div>US</div><div>RoHS</div><div>compliant</div></div></div></div></div></div></div>				<div>Derating diagram acc. to IEC512 (Current carrying capacity)</div> <div><div>Current-carrying capacity</div><div>1,5A @ 40°C</div></div> <div><div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div>Measurement points</div><div>Derating curve</div></div><div><div>Heating</div><div>Derating curve 80%</div></div></div><div><div><div>5,0</div><div>4,0</div><div>3,0</div><div>2,0</div><div>1,0</div><div>0,0</div></div><div><div>0,0</div><div>18,0</div><div>36,0</div><div>54,0</div><div>72,0</div><div>90,0</div></div></div><div><div>Operation Current / A</div><div>Ambient Temperature / °C</div></div><div><div>HARTING KGaA 24.06.2016</div></div></div></div><div><div>The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals.</div><div>The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.</div><div>Control and test procedures according to DIN IEC 60 512.</div></div></div>																																							
<div>General information</div> <table><tr><td>Design</td><td colspan="3">Cable to Board for non ethernet communication e.g. signals & serial bus systems</td></tr><tr><td>Product standard</td><td colspan="3">IEC 61076-3-124 (Type B)</td></tr><tr><td>No. of contacts</td><td colspan="3">10</td></tr><tr><td>Shielding</td><td colspan="3">Fully shielded, 360° shielding contact</td></tr><tr><td>Degree of protection</td><td colspan="3">IP20</td></tr><tr><td>Mating cycles</td><td colspan="3">Min. 5.000</td></tr><tr><td>UL/CSA</td><td>UL 1977 ECBT2.E102079/ CSA-C22.2</td><td colspan="2">No 182.3 ECBT8.E102079</td></tr><tr><td>RoHS-compliant</td><td colspan="3">Yes</td></tr><tr><td>Lead free</td><td colspan="3">Yes</td></tr></table>				Design	Cable to Board for non ethernet communication e.g. signals & serial bus systems			Product standard	IEC 61076-3-124 (Type B)			No. of contacts	10			Shielding	Fully shielded, 360° shielding contact			Degree of protection	IP20			Mating cycles	Min. 5.000			UL/CSA	UL 1977 ECBT2.E102079/ CSA-C22.2	No 182.3 ECBT8.E102079		RoHS-compliant	Yes			Lead free	Yes						
Design	Cable to Board for non ethernet communication e.g. signals & serial bus systems																																										
Product standard	IEC 61076-3-124 (Type B)																																										
No. of contacts	10																																										
Shielding	Fully shielded, 360° shielding contact																																										
Degree of protection	IP20																																										
Mating cycles	Min. 5.000																																										
UL/CSA	UL 1977 ECBT2.E102079/ CSA-C22.2	No 182.3 ECBT8.E102079																																									
RoHS-compliant	Yes																																										
Lead free	Yes																																										
<div>Cable specification</div> <table><tr><td>Cable diameter</td><td colspan="3">5,5 to 7,2 mm</td><td colspan="2">Special Applications Cable</td></tr><tr><td>P/N</td><td>09451819000</td><td>09451819001</td><td>09451819002</td><td>09451819003</td><td>09451819004</td></tr><tr><td>Connection type</td><td>solder</td><td>IDC</td><td>IDC</td><td>IDC</td><td>IDC</td></tr><tr><td>Conductor cross section</td><td>AWG 28 - 22</td><td>AWG 28/7 - 26/7</td><td>AWG 24/7</td><td>AWG 22/7</td><td>AWG 28/7 - 26/7</td></tr><tr><td>Conductor diameter</td><td>max. 1,55 mm</td><td>0,95 - 1,05 mm</td><td>1,1 - 1,25 mm</td><td>1,4 - 1,6 mm</td><td>1,1 - 1,25 mm</td></tr><tr><td>Note:</td><td colspan="5">AWG 24 -depending on cable structure</td></tr></table>				Cable diameter	5,5 to 7,2 mm			Special Applications Cable		P/N	09451819000	09451819001	09451819002	09451819003	09451819004	Connection type	solder	IDC	IDC	IDC	IDC	Conductor cross section	AWG 28 - 22	AWG 28/7 - 26/7	AWG 24/7	AWG 22/7	AWG 28/7 - 26/7	Conductor diameter	max. 1,55 mm	0,95 - 1,05 mm	1,1 - 1,25 mm	1,4 - 1,6 mm	1,1 - 1,25 mm	Note:	AWG 24 -depending on cable structure								
Cable diameter	5,5 to 7,2 mm			Special Applications Cable																																							
P/N	09451819000	09451819001	09451819002	09451819003	09451819004																																						
Connection type	solder	IDC	IDC	IDC	IDC																																						
Conductor cross section	AWG 28 - 22	AWG 28/7 - 26/7	AWG 24/7	AWG 22/7	AWG 28/7 - 26/7																																						
Conductor diameter	max. 1,55 mm	0,95 - 1,05 mm	1,1 - 1,25 mm	1,4 - 1,6 mm	1,1 - 1,25 mm																																						
Note:	AWG 24 -depending on cable structure																																										
<div>Electrical specification</div> <table><tr><td>Rated current</td><td colspan="5">1,5A - (all pins) values at 40°C</td></tr><tr><td></td><td colspan="5">3A - 4 pins of contacts no. 1, 2, 6 and 7</td></tr><tr><td>Rated voltage</td><td colspan="5">50 V AC / 60 V DC</td></tr><tr><td>Contact resistance (100 mA max. (DC or 1000 Hz))</td><td colspan="5">Contact: 30 mΩ max. Shield: 100 mΩ max.</td></tr><tr><td>Insulation resistance</td><td colspan="5">500 MΩ min. (500 V DC)</td></tr><tr><td>Voltage proof</td><td colspan="5">500 V DC (for 1 min. current leakage max. 2 mA)</td></tr></table>				Rated current	1,5A - (all pins) values at 40°C						3A - 4 pins of contacts no. 1, 2, 6 and 7					Rated voltage	50 V AC / 60 V DC					Contact resistance (100 mA max. (DC or 1000 Hz))	Contact: 30 mΩ max. Shield: 100 mΩ max.					Insulation resistance	500 MΩ min. (500 V DC)					Voltage proof	500 V DC (for 1 min. current leakage max. 2 mA)								
Rated current	1,5A - (all pins) values at 40°C																																										
	3A - 4 pins of contacts no. 1, 2, 6 and 7																																										
Rated voltage	50 V AC / 60 V DC																																										
Contact resistance (100 mA max. (DC or 1000 Hz))	Contact: 30 mΩ max. Shield: 100 mΩ max.																																										
Insulation resistance	500 MΩ min. (500 V DC)																																										
Voltage proof	500 V DC (for 1 min. current leakage max. 2 mA)																																										
<div>Pin and pair grouping assignment</div> <table><tr><td>pin assignment</td><td colspan="5">front view of connector Type B</td></tr></table> <div><div><div>jack</div><div><div><div>10</div><div>9</div><div>8</div><div>7</div><div>6</div></div><div><div>1</div><div>2</div><div>3</div><div>4</div><div>5</div></div></div></div><div><div>plug</div><div><div><div>1</div><div>2</div><div>3</div><div>4</div><div>5</div></div><div><div>9</div><div>8</div><div>7</div><div>6</div></div></div></div></div>				pin assignment	front view of connector Type B																																						
pin assignment	front view of connector Type B																																										
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div><div>HARTING</div><div>Department EL PD</div></div></div><div><div>HARTING</div><div>D-32339 Espelkamp</div></div></div><div><div>Scale 1:1</div><div>Free size tol.</div><div>Ref.</div><div>Sub.</div></div><div><div>Created by PREOTU</div><div>Inspected by PREOTU</div><div>Standardisation RUETERA</div><div>Date 2023-07-03</div><div>State Final Release</div></div><div><div>Title HARTING ix Industrial® type B</div><div>Doc-Key / ECM-Nr. 100794076/UGD/000/J 500000248790</div></div><div><div>Type DS</div><div>Number 09450000004</div><div>Rev. J</div><div>Page 1/2</div></div></div>																																											
1	2	3	4	5	6	7	8																																				



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[33481111A20005](#) [33481111A20010](#) [33481111A20015](#) [33481111A20020](#) [33481111A20030](#) [33481111A20050](#)
[09451819001XL](#) [09452819000](#) [09452819000333](#) [33481111A21005](#) [33481111A21010](#) [33481111A21015](#)
[33481111A21020](#) [09451819000XL](#) [09452819002333](#) [09452819002](#) [09451819002XL](#) [33481111A20003](#)
[33481111A20075](#) [33481111A20100](#) [09452819001](#) [33481111A21003](#) [09451819003XL](#)