

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors



1332632  
<https://www.phoenixcontact.com/us/products/1332632>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



USB PCB connectors, degree of protection: IP20, number of positions: 4, 480 Mbps, material: Metal, connection method: Solder connection, USB 2.0

## Your advantages

- Optimized for wave soldering
- Data transmission up to 480 Mbps
- Comfortable tray packing

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1332632       |
| Packing unit                         | 110 pc        |
| Minimum order quantity               | 110 pc        |
| Sales key                            | AB14          |
| Product key                          | ABNDAA        |
| GTIN                                 | 4063151630232 |
| Weight per piece (including packing) | 2.43 g        |
| Weight per piece (excluding packing) | 2.22 g        |
| Customs tariff number                | 85366930      |
| Country of origin                    | CN            |

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors



1332632

<https://www.phoenixcontact.com/us/products/1332632>

## Technical data

### Product properties

|                     |                              |
|---------------------|------------------------------|
| Product type        | Data connector (device side) |
| Type                | USB-A                        |
| Sensor type         | USB 2.0                      |
| Number of positions | 4                            |
| Connection profile  | USB-A                        |
| Type of packaging   | Tray                         |
| Number of slots     | 1                            |
| Type                | Socket                       |
| Shielded            | yes                          |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 00 |
|------------------|----|

### Insulation characteristics

|                      |   |
|----------------------|---|
| Overvoltage category | I |
| Degree of pollution  | 2 |

### Electrical properties

|                                         |                   |
|-----------------------------------------|-------------------|
| Rated voltage (III/2)                   | 30 V              |
| Rated surge voltage (III/2)             | 1500 V            |
| Rated current                           | 1.5 A             |
| Contact resistance                      | 30 mΩ             |
| Frequency range                         | 50 Hz ... 2000 Hz |
| Insulation resistance                   | 1000 MΩ           |
| Transmission medium                     | Copper            |
| Transmission characteristics (category) | USB 2.0           |
| Transmission speed                      | 480 Mbps          |
| Power transmission                      | 45 W              |

### Connection data

#### Connection technology

|                   |                   |
|-------------------|-------------------|
| Connection method | Solder connection |
|-------------------|-------------------|

### Dimensions

|                |          |
|----------------|----------|
| Width          | 14.4 mm  |
| Height         | 7 mm     |
| Length         | 14.9 mm  |
| Orientation to | 180.00 ° |

### Material specifications

|                           |       |
|---------------------------|-------|
| Color of the housing part | black |
|---------------------------|-------|

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors



1332632

<https://www.phoenixcontact.com/us/products/1332632>

|                                        |                  |
|----------------------------------------|------------------|
| Flammability rating according to UL 94 | V0               |
| Housing material                       | Metal            |
| Contact material                       | Copper alloy     |
| Contact surface material               | Gold over nickel |
| Contact carrier material               | PA 4T            |

## Cable/line

|                          |                      |
|--------------------------|----------------------|
| Test voltage Core/Core   | 500 V                |
| Test voltage Core/Shield | 500.00 V             |
| Acceleration             | 3.1 m/s <sup>2</sup> |
| Halogen-free             | yes                  |

## Mechanical properties

### Mechanical data

|                                     |         |
|-------------------------------------|---------|
| Insertion/withdrawal cycles         | > 1500  |
| Insertion force per signal contact  | 35.00 N |
| Extraction force per signal contact | < 10 N  |

## Environmental and real-life conditions

### Test specification

|                                   |                       |
|-----------------------------------|-----------------------|
| Specification                     | EIA 364-1000          |
| Frequency                         | 50-2000 Hz            |
| Sweep speed                       | 1 octave/min          |
| Acceleration                      | 5.40 m/s <sup>2</sup> |
| Test duration                     | 15.00 min.            |
| Contact resistance R <sub>1</sub> | 30.00 mΩ              |

### Test specification

|                                |            |
|--------------------------------|------------|
| Specification                  | 60068-2-27 |
| Acceleration                   | 30.00 g    |
| Number of shocks per direction | 18.00      |

### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Degree of protection            | IP20             |
| Ambient temperature (operation) | -40 °C ... 85 °C |

## Mounting

|               |                |
|---------------|----------------|
| Mounting type | Wave soldering |
|---------------|----------------|

### Processing notes

|                                           |                |
|-------------------------------------------|----------------|
| Process                                   | Wave soldering |
| Classification temperature T <sub>c</sub> | 260 °C         |

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors




1332632

<https://www.phoenixcontact.com/us/products/1332632>

## Drawings

Diagram



Classification wave soldering profile

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors



1332632  
<https://www.phoenixcontact.com/us/products/1332632>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440390 |
| ECLASS-12.0 | 27440390 |
| ECLASS-13.0 | 27460201 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002637 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CUC-USB2.0-J1ST-S/UAF-THT - USB PCB connectors



1332632  
<https://www.phoenixcontact.com/us/products/1332632>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)