


This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.

Customer drawing



RECOMMENDED P.C.B LAYOUT
TOLERANCE: ±0.05MM

REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
1	HK--	First Release Drawing	2013/Oct/17	IP

D-SUB TECHNICAL DATA

SHELL : SPCC, 100u" min tin over 50u" min nickel over 50u" min copper
 BODY : PBT, UL 94V-0, Color:Black.
 CONTACTS : Copper alloy
 Gold flash over 50u" nickel on mating area
 100u" tin over 50u" nickel on solder area
 BRACKET : Zinc alloy, Nickel plated
 BOARDLOCK: Copper alloy. Tin plated
 SCREW: Copper alloy. Nickel plated
 ELECTRICAL : Current rating 3A
 Withstanding Voltage >1000 VAC RMS
 Insulation resistance >1000 M Ohms
 Voltage rating 250 VAC (RMS) Max.
 Contact resistance 25 mOhms max.

PRODUCT CODE

L 17H 2 J 7 0 1 3 1

L: RoHS Compliance

Spacing between ports:
2 - F=19.05mm
G=31.60mm

Top connector:
J = 15Pos. HD Male

Bottom connector:
7 = 15Pos. HD Female

Flange mounting options:
1=4-40unc removable screwlock

Board mounting options:
3= Quad Arrowhead Boardlocks

Shell Plating:
1 = Tin

Contact Plating:
0 = Flash Gold

UNLESS OTHERWISE SPECIFIED TOLERANCES	APPROVAL		DATE
	DRAWN	Checked	2013/Oct/17
U.S. METRIC	0.50	0.30	
.X +/-	0.50	0.30	
.XX +/-	0.30	0.20	
.XXX +/-	0.20		
FRACTIONS +/-			
ANGLES +/-	5°		
FOR MATERIALS AND FINISHES SEE NOTES	DRAWING FILE :		
REMOVE SHARP EDGES	ANGLE OF PROJECTION		
DIMENSIONS			
U.S. INCHES			
METRIC MM			

Amphenol
Amphenol East Asia Limited

TITLE
D-SUB, Dual port type, L17H Series

SIZE	DRAWING NO.	REV.
A4	C L17H2J70131	1
SCALE	NONE	SHEET 1 OF 1