DMC-MR 30-23 SN ACTIVE

DEUTSCH

TE Internal #: ZPF000000000202709

Insert for Contacts, Socket, 30 Pole Configuration, Crimp, Wire-to-

Wire, 30 Position, Sealable, 26 – 22 AWG Wire Size, Rectangular Contact Inserts

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Contact Inserts



Rectangular Connector Insert Type: Insert for Contacts

Contact Type: **Socket**Pole Configuration: **30**

Termination Method to Wire & Cable: Crimp

Connector System: Wire-to-Wire

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Rectangular Connector Insert Type	Insert for Contacts
Connector System	Wire-to-Wire
Sealable	Yes
Configuration Features	
Number of Positions	30

Body Features

Primary Product Material	Composite	
--------------------------	-----------	--

Contact Features

Contact Type	Socket
Pole Configuration	30
Contact Current Rating (Max)	5 A

Termination Features

Mechanical Attachment

Connector Mounting Type Cabl	e Mount (Free-Hanging)
------------------------------	------------------------

Housing Features



Centerline (Pitch)	2.15 mm[.084 in]
Dimensions	
Wire Size	.15 – .4 mm²
Usage Conditions	
Operating Temperature Range	-55 – 175 °C[-67 – 347 °F]
Operation/Application	
Circuit Application	Power, Signal & High Speed Data
Packaging Features	
Packaging Quantity	1
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Pb (1.2% in alloy) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Customers Also Bought



Documents

Product Drawings

DMC-MR 30-23 SN

French

Datasheets & Catalog Pages **DEUTSCH DMCM 30-23 Inserts**

English