T4110012081-000 ACTIVE



M12 Connector

TE Internal #: T4110012081-000

Cable-to-Cable, 8 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard

Circular Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 8

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

Froduct Type realures	
Product Type	Connector Assembly
Accessory Color	Black
Assembly Requirement	Factory Assembled
Assembly Type	Electrical Connector
Circular Connector Shell Type	Metal-Shell
Connector Product Type	Connector Assembly
Connector System	Cable-to-Cable
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Circular Connector Type	Receptacle
Shell Type	Metal
Configuration Features	
Keying & Polarized Position Locations	A

With

Factory Installed Backshell



Keying	A
Number of Positions	8
Number of Power Positions	0
Number of Signal Positions	8
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	30 VAC
Voltage	250 Vrms
Body Features	
Peripheral Seal Material	Silicone
Environmental Protection	IP67
O-Ring Material	Silicone
Environmental Protection Type	Elastomer Sealed
Shell Plating Material	Nickel
Shell Base Material	Copper Alloy
Circular Connector Insulation Material Type	Polyamide 66 GF25
Hermetically Sealed	Yes
Contact Features	
	2 A
Contact Features	
Contact Features Contact Current Rating (Max)	2 A
Contact Features Contact Current Rating (Max) Reverse Gender	2 A Yes
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type	2 A Yes
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features	2 A Yes Socket
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable	2 A Yes Socket
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment	2 A Yes Socket Screw Terminal
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type	2 A Yes Socket Screw Terminal Threaded Coupling
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Mating Alignment	2 A Yes Socket Screw Terminal Threaded Coupling With
Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type	2 A Yes Socket Screw Terminal Threaded Coupling With Cable Mount (Free-Hanging)
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code	2 A Yes Socket Screw Terminal Threaded Coupling With Cable Mount (Free-Hanging) A
Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code Mating Alignment Type	2 A Yes Socket Screw Terminal Threaded Coupling With Cable Mount (Free-Hanging) A



Wire Size	$.525 \text{ mm}^2$
Usage Conditions	
IP Dust Sealing Level	6
IP Water Sealing Level	IP67
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Durability Rating	100 Cycles
Circuit Application	Signal
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94HB
Other	
Position Locations Omitted	0
Field Serviceable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # T4111012081-000 M12 M, 8P GOLD A_CODE S SHIELDED PG9



TE Part # 225297-E M12 MALE, UNI CODE,RA, 8P THR REAR MOUNT



TE Part # 225522-E M12 MALE, A CODE,RA, 8P THR FRONT MOUNT



TE Part # 464676-E M12 MALE, A CODE, 8P, 10.5MM SMT



TE Part # 515632-E M12 MALE, UNI CODE, 8P, 10.5MM SMT, DI



TE Part # 5-2172080-2 M12.MALE.PNLREAR.ACODE.8P. PCBSTD.SRT.SHL



TE Part # 225291-E M12 MALE, A CODE,RA, 8P THR FRONT MOUNT



TE Part # 225294-E M12 MALE, A CODE,RA, 8P THR REAR MOUNT



TE Part # 225295-E M12 MALE, A CODE,RA, 8P THR REAR MOUNT



TE Part # 225454-E M12 MALE, A CODE,RA, 8P THR REAR MOUNT



TE Part # 225521-E M12 MALE, A CODE,RA, 8P THR FRONT MOUNT



TE Part # 225614-E M12 MALE, A CODE,RA, 8P THR REAR MOUNT



TE Part # 235045-E M12 MALE, A CODE,RA, 8P THR REAR MOUNT



TE Part # 254317-E M12 MALE, A CODE, 8P, 10.5MM SMT



TE Part # 284810-E M12 MALE, A CODE, 8P, 10.5MM SMT



TE Part # 364777-E M12 MALE, UNI CODE, 8P, 10.5MM SMT, DI

Cable-to-Cable, 8 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard Circular Connectors











Also in the Series | M12 Connector








Connector Hardware(12)



Connector Seals & Cavity Plugs(4)



M8/M12 Cable Assemblies(230)



Customers Also Bought



TE Part #T4010019041-000 M8, SCREW, FEMALE, S, SHIELD, 4P, GOLD



TE Part #T4111012081-000 M12 M, 8P GOLD A_CODE S SHIELDED PG9



TE Part #T4111512041-000 M12 M, 4P GOLD D_CODE S SHIELDED PG9





TE Part #ZPF000000000008577 983-6S 12-03 SN



TE Part #T4111411041-000 M12 M, 4P GOLD B_CODE S SHIELDED PG7



TE Part #7-1393304-1 V23134M1052C642-EV-CBOX

TE Part #1SNA094320R2600 CPFT2/20

Cable-to-Cable, 8 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard Circular Connectors



TE Part #1SNA179518R0200 IS

Documents

Product Drawings

M12 F, 8P GOLD A_CODE S SHIELDED PG9

English

CAD Files

Customer View Model

ENG_CVM_CVM_T4110012081-000_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4110012081-000_B.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_T4110012081-000_B.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English