

## SCHRACK | SCHRACK Power PCB Relay RT1

TE Internal #: 9-1393239-3


General Purpose Power Relay, Monostable, .4 W Coil, 90 ohm Coil Resistance, UL Coil Insulation Class F, SCHRACK Power PCB Relay

RT1, Power Relays

View on TE.com >



Relays & Contactors > Relays > Power Relays







Relay Type: General Purpose Power Relay

Coil Magnetic System: Monostable

Coil Power Rating DC: .4 W

Coil Resistance: 90 Ω

Coil Special Features: UL Coil Insulation Class F

### **Features**

## **Product Type Features**

Relay Type	General Purpose Power Relay
Configuration Features	
Coil Special Features	UL Coil Insulation Class F
Contact Arrangement	1 Form C SPDT-CO
Contact Number of Poles	1
Electrical Characteristics	
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	30 A
Contact Limiting Continuous Current	16 A
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms
Contact Limiting Breaking Current	16 A
Coil Power Rating DC	.4 W
Coil Resistance	90 Ω
Coil Voltage Rating	6 VDC
Contact Current Rating	16 A
Contact Switching Voltage (Max)	400 VAC
Contact Voltage Rating	250 VAC



#### **Body Features**

Body Features	
Product Weight	14 g[.494 oz]
Contact Features	
Contact Material	AgNi90/10
Termination Features	
Relay Connection Type	PCB Termination
Terminal Configuration	Solder Pins
Mechanical Attachment	
Product Mount Type	Printed Circuit Board
Dimensions	
Insulation Clearance Between Contact & Coil	10 mm[.394 in]
Insulation Creepage Between Contact & Coil	10 mm[.394 in]
Product Width	12.7 mm[.5 in]
Product Length	29 mm[1.14 in]
Product Height	15.7 mm[.618 in]
Usage Conditions	
Usage Conditions  Environmental Category of Protection	RTII
	RTII 85 °C[185 °F]
Environmental Category of Protection	
Environmental Category of Protection  Environmental Ambient Temperature (Max)	
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application	85 °C[185 °F]
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type	85 °C[185 °F]
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process	85 °C[185 °F]  DC  Wave Solder
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System	85 °C[185 °F]  DC  Wave Solder
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System  Packaging Features	85 °C[185 °F]  DC  Wave Solder  Monostable
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System  Packaging Features  Packaging Method	85 °C[185 °F]  DC  Wave Solder  Monostable
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System  Packaging Features  Packaging Method  Other	DC Wave Solder Monostable  Carton, Tube
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System  Packaging Features  Packaging Method  Other  Length Class (Mechanical)	B5 °C[185 °F]  DC  Wave Solder  Monostable  Carton, Tube
Environmental Category of Protection  Environmental Ambient Temperature (Max)  Operation/Application  Current Type  Solder Process  Coil Magnetic System  Packaging Features  Packaging Method  Other  Length Class (Mechanical)  Height Class (Mechanical)	DC Wave Solder Monostable  Carton, Tube  25 – 30 mm  15 – 16 mm

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-

## Compatible Parts



RT78726





















# Also in the Series | SCHRACK Power PCB Relay RT1



# Customers Also Bought















## **Documents**

#### **CAD Files**

Customer View Model ENG\_CVM\_CVM\_9-1393239-3\_E.3d\_igs.zip

English

Customer View Model ENG\_CVM\_CVM\_9-1393239-3\_E.3d\_stp.zip

English



**Customer View Model** 

ENG\_CVM\_CVM\_9-1393239-3\_E.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Power PCB Relay RT1

English

**Product Specifications** 

**Definitions General Purpose Relays** 

English

Agency Approvals

**VDE Certificate** 

English