SOLISTRAND

TE Internal #: 8-34138-2

Parallel Splice, 12 – 10 AWG Wire Size, 3 – 6 mm² Wire Size, Serrated, 3.28 mm [.129 in] Barrel Inside Diameter, 5180 – 13100

CMA Wire Size, Splices

View on TE.com >



Terminals & Splices > Splices











Splice Type: Parallel Splice

Wire Size: 3 – 6 mm²

Sealable: No

Splice Features: Serrated

Features

Product Type Features

Splice Accessory Type	Splice
Splice Type	Parallel Splice
Sealable	No
Compatible With Discrete Wire Type	Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire

Body Features

Product Weight	1.281 g
Splice Features	Serrated

Contact Features

	100 μin
Terminal Plating Material	Tin
Contact Base Material	Copper



Barrel Type	Closed			
Mechanical Attachment				
Wire Insulation Support	Without			
Dimensions				
Outside Diameter	5.74 mm[.226 in]			
Wire Size	5180 – 13100 CMA			
Barrel Inside Diameter	3.28 mm[.129 in]			
Terminal Material Thickness	1.07 mm[.042 in]			
Product Length	8.71 mm[.343 in]			
Usage Conditions				
Insulation Option	Uninsulated			
Operating Temperature Range	170 °C[338 °F]			
Operation/Application				
Compatible With Wire Base Material	Copper			
Industry Standards				
Government Qualified Splice	No			
Packaging Features				
Packaging Quantity	50			

Product Compliance

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Loose Piece



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



TE Part # 58545-1 SOLISTRAND 10-22 DIE ASSY









Customers Also Bought





















Documents

Product Drawings
SPLICE, SOLIS PARA 12-10

English

CAD Files

Customer View Model

ENG_CVM_CVM_8-34138-2_Y.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_8-34138-2_Y.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_8-34138-2_Y.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SOLISTRAND - QRG

English