

DEUTSCH | DEUTSCH DRC

TE Internal #: DRC26-50S08

Housing for Female Terminals, Wire-to-Wire, 50 Position, 4.42 mm [. 174 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DRC Housings



Connector System: Wire-to-Wire

Number of Positions: 50

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4.42 mm [.174 in]

Sealable: Yes

All DEUTSCH DRC Housings (117)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	50
Number of Rows	5
Electrical Characteristics	
Operating Voltage	250 VAC
Nominal Voltage Architecture	250 V
Body Features	
Cable Exit Angle	180°

Black

80

Primary Product Color

Connector & Keying Code



Contact Features	
Contact Size	Size 20
Contact Type	Socket
Mating Pin Diameter	1.02 mm[.04 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	4.42 mm[.174 in]
Dimensions	
Connector Height	36.45 mm[1.435 in]
Product Width	68.58 mm[2.7 in]
Product Length	32.36 mm[1.274 in]
Row-to-Row Spacing	4.42 mm[.174 in]
Compatible Insulation Diameter Range	1.02 – 2.41 mm[.04 – .095 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	125



Packaging Method Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts



TE Part # 1062-20-0622 SOC, SF, SIZE 20, 14-16, NI/NI







TE Part # 1062-20-0322 SOC, SF, SIZE 20, 16-22, SLEVLESS, NI



TE Part # 1062-20-0377 SOC, SF, SIZE 20, 16-22, SLEVLESS, SN



TE Part # 1062-20-0277 SOC, SF, SIZE 20, 16-22, SN/SN



TE Part # CAT-D799-H342 DEUTSCH DRC Headers



TE Part # CAT-D799-B128 **DEUTSCH DRC Backshells**



TE Part # 0411-240-2005 EXT TOOL, SIZE 20, 16-22 AWG, N,



TE Part # 1062-20-0222 SOC, SF, SIZE 20, 16-22, NI/NI



TE Part # 1062-20-0122 SOC, SF, SIZE 20, 16-22, NI/NI



TE Part # 1062-20-0144 SOC, SF, SIZE 20, 16-22, AU/SN



TE Part # 1062-20-0177 SOC, SF, SIZE 20, 16-22, SN/SN



TE Part # 1062-20-0344 SOC, SF, SIZE 20, 16-22, SLEVLESS, AU /SN



TE Part # 1062-20-0644 SOC, SF, SIZE 20, 14-16, AU/SN



TE Part # 1062-20-0677 SOC, SF, SIZE 20, 14-16, SN/SN



TE Part # DRC26-50BT BOOT, 50P, 20SZ, PLG/REC, ST, BLK

TE Part # 0515-018-5005 PROTECT CVR, 38/50/60P, PLG, WHT, DRC20

TE Part # 1060-20-0677 PIN, SF, SIZE 20, 14-16, SN/SN

Also in the Series | DEUTSCH DRC



Automotive Housings(117)



Connector Backshells(6)



Connector Strain Relief(3)



Insertion & Extraction Tools(7)





Customers Also Bought











Documents

Product Drawings

PLG, 50P, BLK, N, 08

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DRC26-50S08_99_c-drc26-50s08-99.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DRC26-50S08_99_c-drc26-50s08-99.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DRC26-50S08_99_c-drc26-50s08-99.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing for Female Terminals, Wire-to-Wire, 50 Position, 4.42 mm [.174 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC



Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Product Specification

English

Agency Approvals

UL Report

English