

PART NUMBER

54144JB-ROCV

Rochester Electronics Manufactured Components

Rochester branded components are manufactured using either die/wafers purchased from the original suppliers or Rochester wafers recreated from the original IP. All re-creations are done with the approval of the Original Component Manufacturer. (OCM)

Parts are tested using original factory test programs or Rochester developed test solutions to guarantee product meets or exceeds the OCM data sheet.

Quality Overview

- ISO-9001
- AS9120 certification
- Qualified Manufacturers List (QML) MIL-PRF-38535
 - Class Q Military
 - Class V Space Level

Qualified Suppliers List of Distributors (QSLD)

- Rochester is a critical supplier to DLA and meets all industry and DLA standards.

Rochester Electronics, LLC is committed to supplying products that satisfy customer expectations for quality and are equal to those originally supplied by industry manufacturers.

The original manufacturer's datasheet accompanying this document reflects the performance and specifications of the Rochester manufactured version of this device. Rochester Electronics guarantees the performance of its semiconductor products to the original OCM specifications. 'Typical' values are for reference purposes only. Certain minimum or maximum ratings may be based on product characterization, design, simulation, or sample testing.

PART NUMBER

54144JB

Rochester Electronics Manufactured Components

Rochester branded components are manufactured using either die/wafers purchased from the original suppliers or Rochester wafers recreated from the original IP. All re-creations are done with the approval of the Original Component Manufacturer. (OCM)

Parts are tested using original factory test programs or Rochester developed test solutions to guarantee product meets or exceeds the OCM data sheet.

Quality Overview

- ISO-9001
- AS9120 certification
- Qualified Manufacturers List (QML) MIL-PRF-38535
 - Class Q Military
 - Class V Space Level

Qualified Suppliers List of Distributors (QSLD)

- Rochester is a critical supplier to DLA and meets all industry and DLA standards.

Rochester Electronics, LLC is committed to supplying products that satisfy customer expectations for quality and are equal to those originally supplied by industry manufacturers.

The original manufacturer's datasheet accompanying this document reflects the performance and specifications of the Rochester manufactured version of this device. Rochester Electronics guarantees the performance of its semiconductor products to the original OCM specifications. 'Typical' values are for reference purposes only. Certain minimum or maximum ratings may be based on product characterization, design, simulation, or sample testing.

PART NUMBER

54144JB

Rochester Electronics Manufactured Components

Rochester branded components are manufactured using either die/wafers purchased from the original suppliers or Rochester wafers recreated from the original IP. All re-creations are done with the approval of the Original Component Manufacturer. (OCM)

Parts are tested using original factory test programs or Rochester developed test solutions to guarantee product meets or exceeds the OCM data sheet.

Quality Overview

- ISO-9001
- AS9120 certification
- Qualified Manufacturers List (QML) MIL-PRF-38535
 - Class Q Military
 - Class V Space Level

Qualified Suppliers List of Distributors (QSLD)

- Rochester is a critical supplier to DLA and meets all industry and DLA standards.

Rochester Electronics, LLC is committed to supplying products that satisfy customer expectations for quality and are equal to those originally supplied by industry manufacturers.

The original manufacturer's datasheet accompanying this document reflects the performance and specifications of the Rochester manufactured version of this device. Rochester Electronics guarantees the performance of its semiconductor products to the original OCM specifications. 'Typical' values are for reference purposes only. Certain minimum or maximum ratings may be based on product characterization, design, simulation, or sample testing.

TYPES SN54143, SN54144, SN74143, SN74144 4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS

NOVEMBER 1971—REVISED DECEMBER 1983

- **Choice of Driver Outputs:**

SN54143 and SN74143 have 15 mA Constant-Current Outputs for Driving Common-Anode LED's such as TIL302 or TIL303 without Series Resistors

SN54144 and SN74144 Drive High-Current Lamps, Numitrons[†], or LED's from Saturated Open-Collector Outputs

- **Universal Logic Capabilities**

Ripple Blanking of Extraneous Zeros
Latch Outputs Can Drive Logic Processors Simultaneously
Decimal Point Driver Is Included

- **Synchronous BCD Counter Capability**

- Includes:**

Cascadable to N-Bits

Look-Ahead-Enable Techniques Minimize Speed Degradation When Cascaded for Large-Word Display

Direct Clear Input

SN54143, SN54144 . . . J OR W PACKAGE
SN74143, SN74144 . . . J OR N PACKAGE
(TOP VIEW)

SCE	1	24	V _{CC}
CLK	2	23	PECI
CLR	3	22	MAX
RBI	4	21	STRB
BI	5	20	QD
BI/RBO	6	19	QC
DP	7	18	QB
dp	8	17	QA
d	9	16	b
f	10	15	a
e	11	14	c
GND	12	13	g

description

These TTL MSI circuits contain the equivalent of 86 gates on a single chip. Logic inputs and outputs are completely TTL compatible. The buffered inputs are implemented with relatively large resistors in series with the bases of the input transistors to lower drive-current requirements to one-half of that required for a standard Series 54/74 TTL input. The serial-count-enable, actually two internal emitters, is rated as one standard Series 54/74 load. The logic outputs, except RBO, have active pull-ups.

The SN54143 and SN74143 driver outputs are designed specifically to maintain a relatively constant on-level sink current of approximately 15 milliamperes from output "a" through "g" and seven milliamperes from output "dp" over a voltage range from one to five volts. Any number of LED's in series may be driven as long as the output voltage rating is not exceeded.

The SN54144 and SN74144 have high-sink-current saturated outputs for driving indicators having voltage ratings up to 15 volts or requiring up to 25 milliamperes drive. The SN54144 sinks 20 milliamperes and the SN74144 sinks 25 milliamperes at an on-level voltage of 0.6 volts across their respective operating temperature ranges.

All inputs are diode-clamped to minimize transmission-line effects, thereby simplifying system design. Maximum clock frequency is typically 18 megahertz and power dissipation is typically 280 milliwatts. The SN54143 and SN54144 are characterized for operation over the full military temperature range of -55°C to 125°C; the SN74143 and SN74144 are characterized for operation from 0°C to 70°C.

3

TTL DEVICES

[†] Trademark of RCA

PRODUCTION DATA

This document contains information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

TYPES SN54143, SN54144, SN74143, SN74144 4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS



description (continued)

Functions of the inputs and outputs of these devices are as follows:

FUNCTION	PIN NO.	DESCRIPTION
CLEAR INPUT	3	When low, resets and holds counter at 0. Must be high for normal counting.
CLOCK INPUT	2	Each positive-going transition will increment the counter provided that the circuit is in the normal counting mode (serial and parallel count enable inputs low, clear input high).
PARALLEL COUNT ENABLE INPUT (PCEI)	23	Must be low for normal counting mode. When high, counter will be inhibited. Logic level must not be changed when the clock is low.
SERIAL COUNT ENABLE INPUT (SCEI)	1	Must be low for normal counting mode, also must be low to enable maximum count output to go low. When high, counter will be inhibited and maximum count output will be driven high. Logic level must not be changed when the clock is low.
MAXIMUM COUNT OUTPUT	22	Will go low when the counter is at 9 and serial count enable input is low. Will return high when the counter changes to 0 and will remain high during counts 1 through 8. Will remain high (inhibited) as long as serial count enable input is high.
LATCH STROBE INPUT	21	When low, data in latches follow the data in the counter. When high, the data in the latches are held constant, and the counter may be operated independently.
LATCH OUTPUTS (QA, QB, QC, QD)	17, 18, 19, 20	The BCD data that drives the decoder can be stored in the 4-bit latch and is available at these outputs for driving other logic and/or processors. The binary weights of the outputs are: QA = 1, QB = 2, QC = 4, QD = 8.
DECIMAL POINT INPUT	7	Must be high to display decimal point. The decimal point is not displayed when this input is low or when the display is blanked.
BLANKING INPUT (BI)	5	When high, will blank (turn off) the entire display and force RB _O low. Must be low for normal display. May be pulsed to implement intensity control of the display.
RIPPLE-BLANKING INPUT (RB _I)	4	When the data in the latches is BCD 0, a low input will blank the entire display and force the RB _O low. This input has no effect if the data in the latches is other than 0.
RIPPLE-BLANKING OUTPUT (RB _O)	6	Supplies ripple blanking information for the ripple blanking input of the next decade. Provides a low if BI is high, or if RB _I is low and the data in the latches in BCD 0; otherwise, this output is high. This pin has a resistive pull-up circuit suitable for performing a wire-AND function with any open-collector output. Whenever this pin is low the entire display will be blanked; therefore, this pin may be used as an active-low blanking input.
LED/LAMP DRIVER OUTPUTS (a, b, c, d, e, f, g, dp)	15, 16, 14, 9 11, 10, 13, 8	Outputs for driving seven-segment LED's or lamps and their decimal points. See segment identification and resultant displays on following page.


3

TTL DEVICES



TYPES SN54143, SN54144, SN74143, SN74144
4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS


logic diagram



TTL DEVICES

TYPES SN54143, SN54144, SN74143, SN74144 4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS

schematics of inputs and outputs



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC} (see Note 1)	7 V
Input voltage	5.5 V
Off-state voltage at outputs "a" thru "g" and "dp", '144	15 V
Off-state current at outputs "a" thru "g" and "dp", '143	250 μ A
Continuous total power dissipation at (or below) 70°C free-air temperature (see Note 2)	1.4 W
Operating free-air temperature range: SN54 ¹ Circuits	-55°C to 125°C
SN74 ¹ Circuits	0°C to 70°C
Storage temperature range	-65°C to 150°C

NOTES: 1. Voltage values are with respect to network ground terminal.
2. For the SN54143 and SN54144 in the N and W packages, this rating applies at (or below) 80°C free-air temperature. For operation above this temperature, derate linearly at the rate of 11.7 mW/°C for the W package and 14.7 mW/°C for the N package. No derating is required for these devices in the J package.

3

TTL DEVICES

recommended operating conditions

			SN54143, SN54144	SN74143, SN74144	UNIT		
	MIN	NOM	MAX	MIN	NOM	MAX	UNIT
Supply voltage, V_{CC}	4.5	5	5.5	4.75	5	5.25	V
On-state voltage at outputs a thru g and dp ('143 only)	1	5	1	5			V
High-level output current, I_{OH}	Q_A, Q_B, Q_C, Q_D			-240		-240	
	Maximum count			-560		-560	μ A
	Bi/RBO			-120		-120	
Low-level output current, I_{OL}	$Q_A, Q_B, Q_C, Q_D, Bi/RBO$			4.8		4.8	mA
	Maximum count			11.2		11.2	
Clock pulse width, $t_{W(clock)}$	High logic level			25		25	
	Low logic level			55		55	ns
Clear pulse width, $t_{W(clear)}$				25		25	ns
Setup time, t_{SU}	Serial and parallel carry			301		301	
	Clear inactive state			601		601	ns
Operating free-air temperature, T_A	-55		125	0		70	°C

¹The arrow indicates that the rising edge of the clock pulse is used for reference.

TYPES SN54143, SN54144, SN74143, SN74144
4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS [†]	SN54143, SN74143			SN54144, SN74144			UNIT
		MIN	TYP [‡]	MAX	MIN	TYP [‡]	MAX	
V _{IH}	High-level input voltage			2			2	V
V _{IL}	Low-level input voltage			0.8			0.8	V
V _{IK}	Input clamp voltage	V _{CC} = MIN, I _I = -12 mA			-1.5		-1.5	V
V _{OH}	High-level output voltage	RBO Q _A , Q _B , Q _C , Q _D Maximum count	V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = 0.8 V, I _{OH} = MAX	2.4		2.4		V
V _{OL}	Low-level output voltage	Q _A , Q _B , Q _C , Q _D , RBO Maximum count	V _{CC} = MIN, V _{IH} = 2 V, V _{IL} = 0.8 V, I _{OL} = MAX		0.4		0.4	V
V _{O(off)}	Off-state output voltage	Outputs a thru g, dp	V _{CC} = MAX, I _{OH} = 250 μ A	7		15		V
V _{O(on)}	On-State output voltage	Outputs a thru g, dp	V _{CC} = MIN, See Note 3				0.6	V
I _{O(on)}	On-state output current	Outputs a thru g	V _{CC} = MIN, V _O = 1 V	9	15			
			V _{CC} = 5 V, V _O = 2 V		15			
			V _{CC} = MAX, V _O = 5 V		15	22		
	Output dp	Output dp	V _{CC} = MIN, V _O = 1 V	4.5	7			mA
			V _{CC} = 5 V, V _O = 2 V		7			
			V _{CC} = MAX, V _O = 5 V		7	12		
I _I	Input current at maximum input voltage	V _{CC} = MAX, V _I = 5.5 V			1		1	mA
I _{IH}	High-level input current	Serial carry			40		40	μ A
		RBO node	V _{CC} = MAX, V _I = 2.4 V	-0.12	-0.5	-0.12	-0.5	mA
		Other inputs			20		20	μ A
I _{IL}	Low-level input current	Serial carry			-1.6		-1.6	
		RBO node	V _{CC} = MAX, V _I = 0.4 V, See Note 4	-1.5	-2.4	-1.5	-2.4	mA
		Other inputs			-0.8		-0.8	
I _{OS}	Short-circuit output current	Q _A , Q _B , Q _C , Q _D	V _{CC} = MAX	-9	-27.5	-9	-27.5	mA
		Maximum count		-15	-55	-15	-55	
I _{CC}	Supply current	V _{CC} = MAX, See Note 5		56	93	56	93	mA

[†] For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.

[‡] All typical values are at V_{CC} = 5 V, T_A = 25°C.

NOTES: 3. For SN54144, I_{OL} = 20 mA; for SN74144, I_{OL} = 25 mA.

4. I_{IL} at RBO node is tested with BT grounded and RBI at 4.5 V.

5. I_{CC} is measured after the following conditions are established:

- Strobe = RBI = DP = 4.5 V
- Parallel count enable = serial count enable = $\overline{BT} = GND$
- Clear (L) then clock until all outputs are on (H)
- For '143, outputs "a" through "g" and "dp" = 2.5 V, all other outputs open. For '144, all outputs are open.

switching characteristics, V_{CC} = 5 V, T_A = 25°C

PARAMETER [§]	FROM (INPUT)	TO (OUTPUT)	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f _{max}				12	18		MHz
t _{PLH}	Serial look-ahead	Maximum count	C _L = 15 pF, R _L = 560 Ω , See Note 6	12	20		ns
t _{PHL}				23	35		
t _{PLH}	Clock	Maximum count	C _L = 15 pF, R _L = 1.2 k Ω , See Note 6	26	40		ns
t _{PHL}				29	45		
t _{PLH}	Clock	Q _A , Q _B , Q _C , Q _D	C _L = 15 pF, R _L = 1.2 k Ω , See Note 6	28	45		ns
t _{PHL}		Clear		38	60		
t _{PHL}	Clear	Q _A , Q _B , Q _C , Q _D		57	90		ns

[§] f_{max} Maximum clock frequency, t_{PLH} Propagation delay time, low-to-high level output,

t_{PHL} Propagation delay time, high-to-low level output

NOTE 6: See General Information Section for load circuits and voltage waveforms.

3

TTL DEVICES


TYPES SN54143, SN54144, SN74143, SN74144 4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS

TTL DEVICES

TYPICAL APPLICATION DATA

This application demonstrates how the drivers may be cascaded for N -bit display applications. It features:

- Synchronous, look-ahead counting
- Ripple blanking of leading zeros; blanking of trailing zeros (not illustrated) can also be implemented
- Overriding blanking for total suppression or intensity modulation of display
- Direct parallel clear
- Latch strobe permits counter to acquire next display while viewing current display



[†]The serial count-enable input of the least-significant digit is normally grounded; however, it may be used as a count-enable control for the entire counter (high to disable, low to count) provided the logic level on this pin is not changed while the clock line is low or false counting may result.

TYPES SN54143, SN54144, SN74143, SN74144 4-BIT COUNTER/LATCH, SEVEN-SEGMENT LED/LAMP DRIVERS

FUNCTION TABLE

FUNCTION	CLOCK PULSE	INPUTS						OUTPUTS						LED/LAMP DRIVERS						TYPICAL NOTES
		CLEAR	LATCH STROBE	BIT	DECIMAL INPUT	PARALLEL CARRY	RFI/RBO	MAXIMUM COUNT OUTPUT	LATCH QD	QC QB	QA	a	b	c	d	e	f	g	dp	
Clear/Ripple Blank		L	L	X	X	X	L	H	L	L	L	OFF	OFF	OFF	OFF	OFF	OFF	OFF	None	
Blank		H	L	X	H	X	L	H	L	L	L	OFF	OFF	OFF	OFF	OFF	OFF	OFF	None	
Decimal	0	H	L	H	L	H	L	H	L	L	H	OFF	OFF	OFF	OFF	OFF	OFF	OFF	A, D, E	
	1	H	L	H	L	L	L	H	L	L	H	OFF	ON	OFF	OFF	OFF	OFF	OFF		
	2	H	L	H	L	L	L	H	L	H	L	ON	OFF	ON	OFF	ON	OFF	OFF	B	
	3	H	L	H	L	L	L	H	L	H	H	ON	ON	ON	OFF	ON	OFF	OFF	B	
	4	H	L	H	L	L	L	H	L	H	L	OFF	ON	OFF	OFF	ON	OFF	OFF	B	
	5	H	L	H	L	L	L	H	L	H	L	ON	OFF	ON	OFF	ON	OFF	OFF	B	
	6	H	L	H	L	L	L	H	L	H	L	ON	OFF	ON	ON	ON	ON	OFF	B	
	7	H	L	H	L	L	L	H	L	H	H	ON	ON	OFF	OFF	OFF	OFF	OFF	B	
	8	H	L	H	L	L	L	H	H	L	L	ON	ON	ON	ON	ON	ON	OFF	B	
	9	H	L	H	L	L	L	H	L	H	L	ON	ON	ON	OFF	ON	ON	OFF	B	
	0	H	L	H	L	L	L	H	H	L	L	ON	ON	ON	ON	ON	ON	OFF	B, C	
	1	H	L	H	L	L	L	H	H	L	L	OFF	ON	OFF	OFF	OFF	OFF	OFF	B	
	2	H	L	H	L	L	L	H	H	L	H	ON	ON	OFF	ON	ON	OFF	OFF	B	
	3	H	L	H	L	L	L	H	H	L	H	ON	ON	ON	OFF	ON	OFF	OFF	B	
	4	H	L	H	L	L	L	H	H	L	H	OFF	ON	ON	OFF	ON	OFF	OFF	B	
	5	H	H	H	L	L	L	H	H	L	H	ON	OFF	ON	ON	ON	OFF	OFF	B	
Latch	6	H	H	H	L	L	L	H	H	L	H	ON	OFF	ON	ON	ON	OFF	OFF	B	
Latch	7	H	H	H	L	L	L	H	H	H	L	ON	OFF	ON	ON	ON	OFF	OFF	B	
	8	H	H	L	H	L	L	H	H	H	L	ON	ON	ON	ON	ON	ON	OFF	B	
	9	H	H	L	H	L	L	H	L	H	L	ON	ON	ON	OFF	ON	ON	OFF	B	
Ripple Blank	0	H	L	L	X	L	L	L	H	L	H	OFF	OFF	OFF	OFF	OFF	OFF	OFF	None	

NOTES: A. RFI/RBO is wire-AND logic serving as ripple blanking input (RFI) and/or ripple blanking output (RBO).

B. The blanking input (BI) must be low when functions DECIMAL/0 through 20/ripple blank are desired.

C. The ripple-blanking input (RFI) must be open or high to display a zero during the decimal 0 input.

D. When a high logic level is applied directly to the blanking input (BI) all segment outputs are off regardless of any other input condition.

E. When the ripple-blanking input (RBO) goes to a low logic level, all segment outputs are off and the ripple-blanking output (RBO) goes to a low logic level (response condition).

SEGMENT IDENTIFICATION



TTL DEVICES

