

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C		STORAGE TEMPERATURE RANGE	-10°C TO 60 °C <sup>(1)</sup>		
	VOLTAGE	50 V AC		OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY 95 % RH MAX. <sup>(2)</sup>		
	CURRENT	0.3 A		STORAGE HUMIDITY RANGE	40 % TO 70 % <sup>(1)</sup>		
SPECIFICATIONS							
ITEM	TEST METHOD		REQUIREMENTS		QT AT		
CONSTRUCTION							
GENERAL EXAMINATION	VISUAL AND WITH MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>		
MARKING	CONFIRM VISUALLY.				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>		
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE [EIA-364-23]	100 mA and 20 mv OPEN CIRCUIT MAX.		11mm height : 95 mΩ MAX. 12mm height : 100 mΩ MAX. 13mm height : 105 mΩ MAX.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
INSULATION RESISTANCE [EIA-364-21]	100 V DC.		100 MΩ MIN.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
VOLTAGE PROOF [EIA-364-20]	150 V AC FOR 1 MINUTE.		NO FLASHOVER OR BREAKDOWN.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>		
MECHANICAL CHARACTERISTICS							
INSERTION AND WITHDRAWAL FORCES [EIA-364-13]	MEASURED BY APPLICABLE CONNECTORS.		INSERTION FORCE: 86.4 N MAX. WITHDRAWAL FORCE: 3.6 N MIN.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
MECHANICAL OPERATION [EIA-364-09]	20 TIMES INSERTIONS AND EXTRACTION.		① CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
RANDOM VIBRATION [EIA-364-28]	FREQUENCY: 20 TO 500 Hz POWER SPECTRAL DENSITY: 0.02 G <sup>2</sup> /Hz OVERALL rms G: 3.1 Grms FOR 15 MINUTES IN THREE DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1μs OR MORE. 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
SHOCK [EIA-364-27]	490 m/s <sup>2</sup> , DURATION OF PULSE: 11 ms 3 EACH DIRECTION, 3 AXIS.				<input checked="" type="checkbox"/> <input type="checkbox"/>		
ENVIRONMENTAL CHARACTERISTICS							
THERMAL SHOCK [EIA-364-32]	TEMPERATURE: -55 → 15 ~ 35 → 85 → 15 ~ 35 °C TIME: 30 → 5 → 30 → 5 min. UNDER 10 CYCLES		1) CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
CYCLIC TEMPERATURE AND HUMIDITY [EIA-364-31]	@ 25 °C, 80% RH: 60 MIN DWELL TIME 30 MIN RAMP TIME @ 65 °C, 50% RH: 60 MIN DWELL TIME UNDER 24 CYCLES.				<input checked="" type="checkbox"/> <input type="checkbox"/>		
DRY HEAT [EIA-364-17]	EXPOSED AT 105 °C, 1000 hr.				<input checked="" type="checkbox"/> <input type="checkbox"/>		
MIXED FLOWING GAS [EIA-364-65]	EXPOSED AT 30 °C, 70% Cl <sub>2</sub> : 10 ppb, NO <sub>2</sub> : 200 ppb, H <sub>2</sub> S : 10 ppb, SO <sub>2</sub> : 100 ppb UNMATED 7 DAYS, MATED 7 DAYS.		1) CONTACT RESISTANCE CHANGE: 20 mΩ OR LESS 2) NO HEAVY CORROSION.		<input checked="" type="checkbox"/> <input type="checkbox"/>		
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED		
					DATE		
REMARK <sup>(1)</sup> THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. <sup>(2)</sup> NO DEW CONDENSATION IS PERMITTED.				APPROVED	MK. EZAKI 14.03.12		
				CHECKED	MK. EZAKI 14.03.12		
				DESIGNED	TS. OSHIDA 14.03.12		
				DRAWN	TS. OSHIDA 14.03.12		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-355706-01		
	SPECIFICATION SHEET		PART NO.	FX10-1441P-44Q-8PH (03)			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL608-0010-4-03	 1/1		