

APPLICABLE STANDARD		SPECIFICATIONS				
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C		STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
				APPLICABLE CABLE	φ 8±0.5 mm	
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING	CONFIRMED VISUALLY.				-	-
ENVIRONMENTAL CHARACTERISTICS						
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.		NO HEAVY CORROSION.		X	-
SEALING ⁽¹⁾	EXPOSED AT A DEPTH OF 1.8 m FOR 48h.		NO WATER PENETRATION INSIDE CONNECTOR.		X	-
AIRTIGHTNESS ⁽¹⁾	APPLY AIR PRESSURE 18 kPa FOR 30s TO INSIDE CONNECTOR		NO AIR BUBBLES INSIDE CONNECTOR		X	-
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	
0						
REMARK				APPROVED	HY. KOBAYASHI	18.03.15
NOTE (1) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.				CHECKED	HY. KOBAYASHI	18.03.15
				DESIGNED	TH. KAMEYA	18.03.15
Unless otherwise specified, refer to IEC 60512.(JIS C 5402)				DRAWN	TH. KAMEYA	18.03.15
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC-110598-31-00
HS	SPECIFICATION SHEET		PART NO.	JR13WCC-8 (31)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2049-1-31	△	1/1