

COAXIAL CONNECTOR, SMA, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_SMA-50-0-13/111_N

Properties

- Excellent return loss
- Intermateable with PC3.5 and SK
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA	jack	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz

Mechanical data	
Weight	0.0013 kg
Mating cycles	500
Flange type	round flange / dia. 5.3
Tab style	Standard

Environmental data	
Operation temperature	-65 °C ... 165°C

Ordering Information Table		
Item number	Item description	Packaging type
22641294	22_SMA-50-0-13/111_NE	Single

COAXIAL CONNECTOR, SMA, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_SMA-50-0-13/111_N

Additional Information	
Remarks	Hermetically sealed: leak rate <= 10^-8 Torr l/s (atm cc/s) dependent on seal processing Panel sealing: laser beam welding

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2776 / Date of publication: 26.11.2023 / uncontrolled copy