

#### HVA 280

TE Internal #: 2103191-2

Housing for Male Terminals, Wire-to-Board / Wire-to-Device, 2 Position, 10.4 mm [.409 in] Centerline, Sealable, Orange, Signal,

HVA 280

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 2

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 10.4 mm [ .409 in ]

Sealable: Yes

### **Features**

#### **Product Type Features**

Product Type Features	
Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	600 VDC

### **Body Features**

Nominal Voltage Architecture

12 V, 24 V, 42 V, 48 V, 80 V, 90 V, 125 V, 240

V, 500 V, 550 V, 600 V



Cable Exit Angle	180°
Primary Product Color	Orange
Connector & Keying Code	В
Contact Features	
Contact Size	2.8mm
Contact Type	Tab
Mating Tab Width	2.8 mm[.11 in]
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	10.4 mm[.409 in]
Dimensions	
Connector Height	27.65 mm[1.08 in]
Product Width	71.55 mm[2.81 in]
Product Length	29.9 mm[1.17 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Other	
Serviceable	No



Connector Position Assurance Capable

Yes

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUN 2015 (163) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts























# Also in the Series | HVA 280



(5)










Electric, Hybrid & Fuel Cell Cable Assemblies(21)



High Voltage Wire Processing Equipment(7)



Other Automotive Connector Accessories(35)




PCB Headers & Receptacles(22)

## Customers Also Bought



REC, 21P, BLK, E, RNG, 12/16, S





TE Part #2-2141598-2 TAB 2.8x0.8 CONTACT CF SRC Ag

















### **Documents**

**Product Drawings** 

CAP SUBASSY, KEY B, HVA280-2PHI

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2103191-2\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2103191-2\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2103191-2\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English