

Home > Products > Relays > Product Feature Selector > Product Details

JMSCD-5XL Product Details

 Share

 Print

 Email



JMSCD-5XL (6-1617351-7)

TE Internal Number: 6-1617351-7

 Active

Military/Aerospace High Performance Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- MSD TO-5 Relay Series
- Input Voltage = 5 VDC
- Contact - Arrangement = 2 Form C, DPDT, 2 C/O
- Contact - Rated Current = 1 A
- Non Polarized, Monostable Coil - Magnetic System

[View all Features](#)

Quick Links

- [Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

 [Add to My Part List](#)

 [Request Sample](#)

 [Find Similar Products](#)

 [Buy Product](#)

Documentation & Additional Information	
Product Drawings: - None Available Catalog Pages/Data Sheets: RELAY (PDF, English) Product Specifications: - None Available Application Specifications: - None Available Instruction Sheets: - None Available CAD Files: - None Available	Additional Information: Product Line Information Related Products: Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: - MOSFET Driver = Without Mechanical Attachment: - Mounting Options = PC Board Electrical Characteristics: - Input Voltage (VDC) = 5 - Contact - Rated Current (A) = 1 - Coil Suppression Diode = With - Coil Polarity Protection Diode = Without - Coil - Resistance (Ω) = 100 - Coil Power Measurement = Milliwatts - Coil - Rated Power, DC (mW) = 250 - Actuating System = DC - Shock = 75 G's, 6ms - Vibration = 30G's, 10 to 3000Hz Termination Features: - Termination Type = Long Leads	Body Features: - Enclosure Type = Hermetically Sealed Configuration Features: Contact - Arrangement = 2 Form C, DPDT, 2 C/O - Coil - Magnetic System = Non Polarized, Monostable - Transistor Driver = Without Industry Standards: - Government/Industry Qualification = Yes - Government/Industry Part Number = M39016/16-033L RoHS/ELV Compliance = Not ELV/RoHS compliant Lead Free Solder Processes = Not suitable for lead free processing - Approved Standards = M39016 Qualified, L Level Conditions for Usage: - Temperature Range (°C) = -65 - +125 Other: Series = MSD TO-5 Relay - Brand = CII

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed



Feedback

